THE NEW JERSEY TURNPIKE AUTHORITY PROCUREMENT AND MATERIALS MANAGEMENT DEPARTMENT

New Jersey Turnpike Administrative Offices 1 Turnpike Plaza P.O. Box 5042 Woodbridge, New Jersey 07095-5042 Tel. - 732-750-5300 Ext. 8640

REQUEST FOR BID

TTTLE:	SINGLE ENGINE BROOM STREET SWEEPER	
BID NO:	<u>R-177573</u>	
DUE DATE:	April 12, 2023	
TIME:	11:30 AM	
SUBMIT BIDS BEFO	ORE THE DUE DATE AND TIME STATED ABOVE TO THE ABOVE ADDRE	<u>ESS</u>
	BIDDER INFORMATION (PLEASE PRINT)	
	NAME OF BIDDING ENTITY	
	ADDRESS	
	CITY, STATE AND ZIP CODE	
	E MAH. ADDDEGG	
	E-MAIL ADDRESS	
DEDDECENITATIVE	TO CONTACT-NAME & TITLE TELEPHONE NO.	
KERKESENTATIVE	TO CONTACT-NAME & TITLE TELEPHONE NO.	

TAXPAYER I.D. NO.

FAX

FEDERAL TAX I.D. NO. or

SECTION I

A. <u>INTRODUCTION</u>

The New Jersey Turnpike Authority (the "Authority") was created by an act of the New Jersey Legislature in 1948, known as the New Jersey Turnpike Authority Act (as amended and supplemented, "Act"). The Act authorizes the Authority to construct, maintain, repair, and operate the New Jersey Turnpike, to collect tolls, and to issue Turnpike Revenue Bonds or Notes, subject to the approval of the Governor, payable from tolls and other revenues of the Authority. On May 27, 2003, the Act was amended to empower the Turnpike to assume all powers, rights, obligations and duties of the New Jersey Highway Authority (the "Highway Authority"), which owned and operated the Garden State Parkway and PNC Bank Arts Center. On July 9, 2003, the Authority assumed all powers, rights, obligations and duties of the Highway Authority. The Authority currently operates both the Garden State Parkway ("GSP") and the New Jersey Turnpike ("Turnpike") (both roads are collectively referred to herein as the ("Roadways").

The Authority is governed by an eight-member Board of Commissioners ("Board"). The Governor of New Jersey appoints each of its members and has the statutory authority to overturn an action of the Board by vetoing any Board action within 10 days of receiving the minutes of the meeting. The Board authorizes awards of all public contracts over \$100,000, except in cases where it has delegated authority to the Executive Director.

This bid solicitation is being conducted pursuant to the Authority's enabling statute as found in *N.J.S.A.* 27:23-6.1 and Executive Order number 37 (Corzine 2006) and the regulations and policies of the Authority regarding public bid procurement.

BIDDER GUIDELINES/CHECKLIST

BIDS THAT FAIL TO CONFORM TO THE FOLLOWING REQUIREMENTS MAY BE REJECTED:

1.	The Request for Bid ("RFB"), including specifications and related bid documents ("Bids") must be received at or before the due
	date and time stated on the cover page at the following place: New Jersey Turnpike Authority, Administration Building, 1 Turnpike
	Plaza, Woodbridge, New Jersey 07095. LATE BIDS WILL BE RETURNED UNOPENED. ELECTRONIC, EMAILED OR
	FACSIMILE BIDS WILL NOT BE ACCEPTED. Bid opening will take place via teleconference call only. See page 5.

- 2. The entity submitting a Bid ("Bidder") must provide one original and one copy of the Bid. The Bid must include all price information. Bid prices shall include delivery of all items F.O.B. destination or as otherwise provided. Price quotes must be firm through issuance of contract.
- 3. All Bid prices must be typed or written in ink. Quote the specified unit of measure. If bidding an alternate, provide detailed specifications on the exception form attached.
- 4. All corrections, white-outs, erasures, re-striking of type, or other forms of alteration or the appearance of alteration, to unit and/or total prices must be initialed in ink by the Bidder.

5.	IF CHECKED, THIS RFB REQUIRES THE FOLLOWING MANDATORY DOCUMENT(S) BE SUBMITTED WITH
	THE BID. FAILURE TO COMPLY WILL RESULT IN REJECTION OF THE BID.

(a) Bid Bond, Letter of Surety or a Cashier's Check for 10% of the amount Bid	\boxtimes
(b	Ownership Disclosure Statement (Exhibit C, Instruction to Bidders page 23)	\boxtimes
(c) Disclosure of Investment Activities in Iran (Exhibit G-1, Instruction to Bidder page 33)	\boxtimes
(d	Vendor Disclosure Form (Exhibit G, Instruction to Bidder page 32)	\boxtimes

6. TO FACILITATE THE CONTRACT AWARD PROCESS, THE FOLLOWING DOCUMENTS SHOULD BE SUBMITTED WITH THE BID. IN THE EVENT THE DOCUMENTS ARE NOT SUBMITTED WITH THE BID, THEY SHALL BE SUBMITTED WITHIN THREE (3) BUSINESS DAYS FOLLOWING A VERBAL OR WRITTEN REQUEST FROM THE AUTHORITY.

(a)	Certification of Registration with the Secretary of State (only if non-NJ corporation)	\times
(b)	Acknowledgement of requirement for Disclosure of Political Contributions (ELEC)	X
(c)	SBE/WBE/MBE/VOB/DVOB Certificates and Form	\boxtimes
(d)	Bidder must sign the Bid	\boxtimes

7. SEE THE AUTHORITY'S INSTRUCTION TO BIDDERS (ATTACHED) FOR A COMPLETE LIST OF THE AUTHORITY'S STANDARD CONTRACT TERMS AND CONDITIONS, AS WELL AS OTHER FORMS THAT ARE REQUIRED PRIOR TO THE AWARD OF THE CONTRACT(S). THE RECOMMENDED LOW BIDDER(S) MUST SUBMIT THE FOLLOWING CHECKED DOCUMENTS PRIOR TO CONTRACT AWARD.

(a)	Mandatory Equal Employment Opportunity Language	\times
(b)	Affirmative Action Information Sheet with Certificate or Form AA302	\boxtimes
(c)	State Contractor Political Contributions Compliance Public Law 2005, Chapter 51 & EO 117	\boxtimes
(d)	Notice to All Bidders of Set-Off for State Tax	\boxtimes
(e)	Insurance Certificate	\boxtimes
(f)	State of New Jersey Division of Business Registration Certificate	\boxtimes
	Russia Interim Certification (P.L. 2022, C.3) Instruction and agreement for Direct Payment (ACH)	\boxtimes

SECTION II

A. INTENTION

- 1. **Sealed Bids** (<u>Paper Submission Only</u>) for R-177573 must be received at the New Jersey Turnpike Authority Administrative Offices, 1 Turnpike Plaza, Woodbridge, New Jersey 07095-5042.
- 2. Bidders mailing Bids should allow for their normal mail delivery time to ensure timely receipt of the Public Bids. Please be advised that using an overnight/next-day delivery service does not guarantee overnight/next-day deliveries to our location. The Authority will not be responsible for any Bid not being received by the required date and time.
- 3. It is the intention of the Authority to issue a Purchase Order for the procurement of ONE (1) SINGLE ENGINE BROOM STREET SWEEPER.
- 4. Items purchased under this contract will be delivered as directed by the Authority.
- 5. Please contact RICHARD BAVA with any questions regarding this procurement at bava@njta.com.

B. BID SHEET INSTRUCTIONS

- 1. Bidders must follow all instructions in this RFB and in the Instructions to Bidders issued by the Authority, and any other documents issued by the Authority regarding this RFB (collectively, "Bid Documents").
- 2. Bidders must examine the bid documents carefully before bidding and must ask the Director of Procurement and Materials Management Department ('PMM") in writing for any interpretation or correction of any apparent ambiguity, inconsistency, or apparent error therein. If necessary, an interpretation or correction to the specifications in the form of an addendum shall be issued at least three (3) days prior to the bid opening by the Director of PMM to Bidders who have obtained the Bid Documents in accordance with *N.J.A.C.* 19:9-2.2(a)(3). **Requests for interpretation or correction shall be considered only if received at least 5 business days prior to the Bid opening date**.
- 3. The submission of the Bid is conclusive evidence that the Bidder is fully aware of the conditions, requirements, and details as stated in the Bid Documents. If the Bidder, prior to submitting its Bid, fails to notify the Director of PMM of the existence of an ambiguity or inconsistency in the Bid Documents, a Bid will conclusively be presumed to have been based upon the Authority's interpretation of such ambiguity or inconsistency.
- 4. All erasures, interpolations or other physical changes on the Bid form shall be signed or initialed by the Bidder. Bids containing any conditions, omissions, erasure's, alterations, or items not called for in this "RFB" or irregularities of any kind, may be rejected by the Authority, in its sole discretion.
- 5. The Bidder shall not attach conditions, limitations, or provisos to its Bid.

6. The Authority will accept Approved Equivalent items on this Bid. If a Bidder is basing the RFB on items other than what is specified, and wishes the items proposed to be considered as an "Approved Equivalent", the Bidder shall enter a price on the Bid sheet then submit on the Exception Form in the exact format of the line item on the RFB contained herein, the item number, an item description including manufacturers name, model number, informational brochure(s), and packaging quantities of those items that the Bidder proposes to substitute.

C. BASIS OF AWARD

- 1. Bidders must supply a price for every item listed. <u>Bids not having a price for all listed items may be rejected.</u>
- 2. Bidders must quote only one price per line item. <u>If a Bidder quotes multiple prices per line item</u>, the Bid may be rejected.
- 3. The Authority will purchase amounts of any given item as needed, at the sole discretion of the Authority and shall not be bound by any quantities listed. The Authority reserves the right to make reasonable increases to line-item quantities.
- 4. All items are to be Bid FOB Destination. All shipping, handling, and other costs should be considered in the Bid price(s).
- 5. The Authority is tax exempt from New Jersey Sales and Excise Tax.
- 6. Award will be made to the lowest responsible and responsive bidder for the total line items Bid.

D. MISCELLANEOUS

- 1. ELECTRONIC PAYMENT: The Vendor will be required to accept <u>payment(s)</u> for goods or <u>services via automatic deposit</u> from the Authority. <u>NO OTHER FORM OF PAYMENT WILL</u> <u>BE PROVIDED.</u> <u>See Exhibit M in the Instructions to Bidders on the Authority's website for the required electronic payment forms: http://www.njta.com/doing-business/goods-and-services</u>
- 2. BID OPENING INFORMATION:

Please be advised that the public bid opening for Solicitation R-177573 which is scheduled for April 12, 2023 @ 11:30AM will be by CONFERENCE CALL ONLY.

Conference call details are as follows:

Dial-in Number: 646-992-2010 Access Code: 2343 839 9805

For any bidder who wishes to participate, conference call access will be open 5 minutes prior to bid opening and remain open until all bids have been read.

E. BID QUOTATION SHEET

ITEM	QTY	UNIT	DESCRIPTION	UNIT PRICE	TOTAL BID AMOUNT
1	1	EA	SINGLE ENGINE BROOM STREET SWEEPER, AS PER ATTACHED SPECIFICATIONS.	\$	\$

Number of days, after receipt of a Purchase Order, that all equipment will be delivered to the Authority, fully completed and compliant with the Specifications:

____ DAYS

Award will be made to the lowest responsive and responsible bidder for the Total Bid Amount.

ANY INQUIRIES CONCERNING THIS BID MUST BE SENT VIA EMAIL TO: bava@njta.com

<u>PURSUANT TO N.J.A.C.</u> 19:9-2.2 (a)(3), ADDENDA WILL BE DISTRIBUTED AND POSTED ON THE AUTHORITY'S WEBSITE AT LEAST THREE DAYS PRIOR TO THE BID OPENING.

NEW JERSEY TURNPIKE AUTHORITY

Very truly yours,

Janet Rzepka, Acting Director Procurement and Materials Management

	/	
Name of Company		Authorized Signature of Bidder

F. SIGNATURE PAGE

1.	ADDENDA / INQUIRIES: COM Receipt of Addendum / Inquiries Receipt of Addenda / Inquiries must	#dated #dated ENDA/INQUIRY ISSU	_ is hereby acknowledged is hereby acknowledged. JED	
2.	BID IRREVOCABLE: This offer which the Authority publicly open has filed a bid protest pursuant to required to hold their prices for a action taken by the Authority.	ns this Bid except in tho to <i>N.J.A.C.</i> 19:9-2.12. U	se instances where an unsucce Jpon notification of a protest,	essful Bidder Bidders are
3.	OFFER/CERTIFICATION: The undersigned offers and agrees to furnish to the New Jersey Turnpike Authority the services and/or materials in compliance with all terms, conditions, specifications, and addenda of the RFB, Bid Documents, and resulting contract. The undersigned further certifies understanding and compliance with the requirements of the standard terms and conditions as stated in the Instructions to Bidders included with the Bid Documents. The undersigned certifies that he or she executes this Bid with full authority so to do; and that all statements contained in this Bid and in this certification, are true and correct, and made with full knowledge that the Authority relies upon the truth of the statements contained herein and, in any statements, requested by the Authority showing evidence of qualifications in awarding the contract. I certify that the foregoing statements made by me are true. I am aware that if any of the foregoing statements made by me are willfully false, I am subject to punishment.			
4.	AUTHORIZED SIGNATURE:			
	Print Name and Title:			
	Bidder:			
	Address:			
	City, State, Zip:			
	E-mail address:			
	Telephone #:	Fa	ax: #	
	Date:	_		

SECTION III

ADDITIONAL YEARS PURCHASING OPTION

BID TITLE: SINGLE ENGINE BROOM STREET SWEEPER

BID NUMBER: R-177573

<u>3 - Year Open End Option</u>: The Authority shall have the option for one (1) Model Year* from the date of Contract, to order additional units conforming to the requirements of these specifications at the same price and under the same terms and conditions as those contained herein.

The Authority shall further have the option to purchase additional units conforming to these specifications for two (2) additional Model Years. Any unit(s) offered during the two (2) subsequent Model Years shall be of the model equivalent to that specified herein. In the latter instances, if there have been any price changes, the vendor shall submit a request to the Authority covering the aforesaid price changes and shall include appropriate explanation and justification for any such price changes.

Any such request for price adjustment shall be in writing and directed to the Director, Procurement and Materials Management Department and shall be accompanied by the following evidence as a basis for your request.

- 1. The published price lists for equipment, which were in effect at the time of your original proposal.
- 2. The equivalent published price lists in effect at the time of your request.
- 3. Any additional evidence which the Authority deems necessary in the evaluation of your request.

The Authority shall, within its sole discretion, have the right to accept the price changes proposed by the vendor or if it so desires, re-bid the requirement.

Model Year is defined as the Model Year of the Manufacturer of the unit(s) offered by you in this Request for
Quotation. In that instance where proposals are for equipment for which "Model Year" and "Production Cut-Off
Dates" are undefined or non-existent, the "Model Year" is defined, for bid purposes, as one calendar year from
he date on which the Contract is accepted. The last date on which orders may be placed for the Model currently
n effect is
N CC 1 / A (1 : 16: (CD:11
Name of Company and / Authorized Signature of Bidder

SECTION IV

NO RESPONSE BID SURVEY

BID REQUISITION NUMBER: R-177573

BID TITLE: SINGLE ENGINE BROOM STREET SWEEPER

If you do not choose to respond to this Bid, please complete this form and email to Richard Bava at: bava@njta.com

Name of Company
Reason you did not respond (Check all that apply)
Cannot supply product or service
Cannot meet technical specifications
Cannot meet delivery specifications
Cannot meet legal requirements (i.e., Bid/performance/security/insurance, etc.)
Cannot provide a competitive price now
Interested in receiving specifications for informational purposes only
Insufficient lead time to respond
Other:(please be specific)
Do you wish to remain on our mailing list?
YesNo
Additional comments:
Signed :(optional)
Company:

SECTION V

NEW JERSEY TURNPIKE AUTHORITY

GENERAL INSTRUCTIONS AND SPECIFICATIONS FOR:

QUANTITY: One (1)

DESCRIPTION: SINGLE ENGINE BROOM STREET SWEEPER

SPECIFICATIONS: SEBSS-2023: SINGLE ENGINE BROOM STREET SWEEPER

<u>COMPLIANCE WITH RULES AND REGULATIONS</u>: The unit and associated equipment furnished must comply with all Federal and State Motor Vehicle Safety Laws and Regulations and shall be capable of passing the New Jersey State Motor Vehicle Inspection Laws, where applicable.

ENERGY STAR REQUIREMENTS: If applicable for items specified in the bid package, the vendor must provide products that earn Energy Star Certification and meet the Energy Star specifications for energy efficiency. The vendor is encouraged to visit energystar.gov for complete product specifications and updated lists of qualifying products. The Energy Star label must also be affixed to each delivered item. The bidder's signature on the signature page certifies that items so indicated that have earned Energy Star and meet the Energy Star specifications or other standards for energy efficiency will be supplied.

ERRORS AND OMISSIONS: Inadvertent omissions or errors in the attached specifications must be brought to the attention of the New Jersey Turnpike Authority's Director of Procurement and Materials Management via email from the vendor to Janet Rzepka (Acting Director of Procurement and Materials Management) at Rzepka@njta.com (5) five days prior to the bid submission date. If, with knowledge of such error or omission and prior to the correction thereof, the bidder proceeds with any work affected hereby, they shall do so at their own risk and the work so done shall not be considered as work done under and in performance of this Agreement unless and until approved and accepted.

<u>QUESTIONS</u>: Questions, which arise before the bid opening, shall be addressed in writing via e-mail from the vendor to Janet Rzepka (Acting Director of Procurement and Materials Management) at <u>Rzepka@njta.com</u> at the New Jersey Turnpike Authority (5) five days prior to bid opening. Questions shall be from the prime bidder only, no subcontractors.

<u>DELIVERY DATE</u>: All bidders <u>must</u> list on their "Bid Quotation Sheet" in the space specified the number of days (e.g., 120, 150, 180, etc. after receipt of purchase order) that all vehicles or equipment will be delivered to the Authority fully completed and fully compliant with the specifications. A <u>specific</u> number of days <u>must</u> be listed. Under <u>no</u> circumstances shall bidders give approximate dates or ranges of dates to deliver such as: 210 days to 240 days. FAILURE TO FOLLOW THESE GUIDELINES MAY RESULT IN REJECTION OF BID.

<u>CONFIRMATION OF ORDER</u>: Once the Vendor receives the purchase order via email from the Authority's representative, the Vendor shall have a maximum of thirty (30) days to **verify in writing** to the Authority that the vehicles or equipment have been placed on order with the manufacturer of said vehicle (s) or equipment. **FAILURE TO FOLLOW THESE GUIDELINES MAY RESULT IN REJECTION OF PURCHASE ORDER AND AWARD TO THE NEXT LOWEST RESPONSIBLE BIDDER.**

DELIVERY INSTRUCTIONS:

Vendor must contact Rich Schneider (Project Supervisor) at 609-426-6300 ext. 8649 for authorization to schedule date and time prior to delivery. Deliveries shall be made to:

New Jersey Turnpike Authority District 4 Maintenance Facility Exit 8 NJ Turnpike and Route 33 Hightstown, NJ 08520

- A. Vendor shall be responsible for all delivery, shipping, and pick-up expenses.
- B. All units must be pre-delivery serviced, completely assembled, operational, and cleaned prior to Authority delivery.
- C. The following administrative package **must** accompany all deliveries:
 - <u>Certificate of Origin</u>: All New Jersey Manufacturers, Dealers, and/or Distributors <u>must</u> stamp the C.O. "Sales Tax Satisfied". The C.O. shall be made out to New Jersey Turnpike Authority, P.O. Box 5042, Woodbridge, NJ 07095. Certificate of Origin shall have current date and be hand delivered to Rich Schneider after final acceptance of complete order.
 - Out of Country Certificates of Origin shall <u>not</u> be acceptable. Awarded vendors outside the United States must use their United States Distributor to fill out Certificates of Origin. NO EXCEPTIONS
 - <u>Invoice</u>: purchase order number must be displayed on vendor's invoice. Invoice shall have current date and be hand delivered to Rich Schneider after final acceptance of complete order.
 - Warranty forms properly executed.
 - Four (4) keys for each vehicle shall be furnished. **NO EXCEPTIONS**
 - It shall be the responsibility of the awarded vendor that all tolls, when applicable be paid when making delivery to the Authority.
- D. Deliveries made directly to the Authority from the manufacturer shall not be acceptable unless manufacturer is awarded bidder.
- E. In the event the awarded bidder contracts a trucking/delivery company to deliver units, a representative from the awarded bidder's company must be at the delivery site at time of delivery to the Authority. **NO EXCEPTIONS**

WARRANTY: All units delivered must be guaranteed to be free from defects in materials, design, and workmanship for a minimum of one (1) year (see additional warranties in specification) and shall start from the time of written acceptance by the New Jersey Turnpike Authority. Warranty must include service availability from any manufacturers authorized dealer establishment most closely located to Parkway and Turnpike area. This repair facility may not be further than 100 miles from District 5 Telegraph Hill Central Maintenance Facility in Holmdel, NJ 07733 or District 4 Maintenance Facility located in Hightstown, NJ 08520. If warranty service is required, the vendor who supplied the unit shall provide for pickup, delivery, and repair of unit at no charge to the New Jersey Turnpike Authority. All warranty periods shall start from date of written acceptance of the unit by the New Jersey Turnpike Authority.

EXCEPTION SHEET: Exception sheet is furnished with each set of specifications. Bidders making exceptions must note exceptions by item and indicate substitution in lieu and submit with bid, detailed specifications on the substitution. If the vendor is submitting an alternate product, component, feature, or part to what is referenced in the specifications, the proposals <u>must</u> be accompanied by descriptive literature, marked, and indicate the exact items to be furnished, with an engineering drawing of the same. Failure to supply information requested may result in rejection of bid. Where no exception is taken; the word "None" shall be neatly printed or typed on the exception sheet. Failure to supply information and/or failure to complete the bidder's exception spaces in the prescribed manner may disqualify bid. It shall be understood that if no exception is taken, the vendor shall supply all material exactly as specified. No substitution will be permitted after receipt of bids.

<u>APPROVED EQUIVALENT</u>: A bid substitution for a specified item brand and/or model that meets the required quality and performance standards of the original brand; substitutions will be determined to be an approved equivalent by the New Jersey Turnpike Authority.

<u>UNIT INFORMATION FORM</u>: Vendor shall complete the entire Unit Information Form. **Failure to complete form may result in rejection of bid.**

MANUFACTURER'S PRODUCTION SHEET: The vendor shall furnish one (1) copy of the actual Factory Production Sheet for each unit provided. The copies of the Factory Production Sheet shall be submitted at the time of the Authority's inspection of the unit.

TRAINING: It shall be the responsibility of the successful bidder to supply all safety, operational and service training to New Jersey Turnpike Authority personnel in accordance with all applicable ANSI and OSHA regulations. The safety and operational training shall consist of a complete review and understanding of the manufacturer's owner manual, along with actual operation of equipment. The instructor shall emphasize all proper uses for safe operation. The training shall include but not limited to all general troubleshooting of the hydraulic system and associated electronics. The instructor shall also emphasize the proper use of tools and test equipment along with general shop safety. The service seminars shall be similar to factory and manufacture type schools. The training, if needed by the Authority shall be scheduled and take place at one (1) site, approximately (8) hours designated by the New Jersey Turnpike Authority.

LABELS: Plastic stick-on labels shall not be acceptable.

ADVERTISEMENTS: No **Dealer** advertisements shall appear on unit or any other related equipment.

NOTICE TO BIDDERS: Bidders shall **not** be allowed to use vehicles/equipment in any type of shows, conventions, brochures, etc. without prior written consent of the New Jersey Turnpike Authority. **NO EXCEPTIONS**

ACCESSORIES: All accessories shall be manufacturer installed when the item is available from the manufacturer.

<u>FACILITIES</u>: Bidders shall represent a manufacturer, which has in operation a factory adequate for the manufacture of the equipment, which it proposes to furnish. The manufacture(s) whose associated equipment or products are bid shall have a full-service warranty and parts supply facility that can guarantee availability of parts within 24 hours after telephone order and shall be located within a 100-mile radius of either District 4 Maintenance Facility (exit 8 on the NJ Turnpike) located in Hightstown, NJ 08520, or Telegraph Hill Central Maintenance Facility (exit 116 on the GSP) located in Holmdel, NJ 07733. The bidder shall submit the locations, names and telephone numbers of people who are authorized to service the equipment or who can be reached for emergency service.

Location		
Phone #		
Contact		
	Name & Title	

SPECIFICATIONS: SEBSS-2023 SINGLE ENGINE BROOM STREET SWEEPER

<u>INTENT</u>: The intent of this specification is to describe and govern the purchase of a 2023 or new current model broom street sweeper having a 6-wheel conventional cab-chassis, 5.4 cubic yard hopper, single engine design, automatic transmission, dual-steering, operator controls, full width belt conveyor, left-side and right-side broom with variable down pressure controlled from the cab and accessories.

BIDDER'S INSTRUCTIONS

IT SHALL BE THE BIDDER'S RESPONSIBILITY TO CAREFULLY EXAMINE EACH ITEM OF THE SPECIFICATION. BIDDERS MUST INDICATE WHETHER THEY COMPLY OR NON-COMPLY FOR EACH LINE ITEM IN THE SPECIFICATION. FAILURE TO PROVIDE A COMPLETED BID MAY CAUSE REJECTION OF BID. ALL NON-COMPLY RESPONSES AND/OR BIDDERS PROPOSED "APPROVED EQUIVALENTS" MUST BE FULLY EXPLAINED ON EXCEPTION FORM, NOTING SECTION AND ITEM. FAILURE TO EXPLAIN NON-COMPLY RESPONSES OR FAILURE TO SUPPLY DETAILED LITERATURE/BROCHURES ON THE BIDDERS PROPOSED "APPROVED **EQUIVALENTS**" MAY **CAUSE** REJECTION OF BID. WHERE "MINIMUM/MAXIMUM" IS SPECIFIED, BIDDERS MUST PROPOSE AT LEAST THE MINIMUM/MAXIMUM SIZES OR THE BID MAY BE REJECTED.

	COMPLY	
	YES	NO
GENERAL:		
A. 2023 or new current model broom street sweeper having a 6-wheel conventional cab-chassis, 5.4 cubic yard hopper, single engine design, automatic transmission, dual-steering, operator controls, full width belt conveyor, left-side and right-side broom with variable down pressure controlled from the cab and accessories.		
B. The complete unit shall be new and of the latest design and be in current production at the time of the submission of bid.		
C. All standard and optional equipment shall be Original Equipment Manufacturer (OEM) items, when available. NO EXCEPTIONS		
D. Bidders must submit with their bid, detailed specifications, along with pictures and brochures of their complete unit being bid. NO EXCEPTIONS		
TRUCK CHASSIS:		
A. 2024 or new current model two-door cab/chassis Freightliner Model M2 or Authority approved equivalent.		
B. 33,000 lbs. minimum G.V.W.R.		
C. Wheelbase: 136".		
D. Outside width in transport mode: 8' maximum.		
E. Overall height: 9'.		
F. Chassis shall have the capability of safely propelling the sweeper loaded to maximum G.V.W.R. under all sweeping and transport conditions.		

	COM	PLY
	YES	NO
G. Vehicle shall be rated for carrying an 11,000 lbs. load in the hopper at highway speed of 55 MPH and should not be speed restricted by tire limitations.		
H. Speed: 65 mph governed.		
I. Sweeping noise level: 79 dba maximum at 50'.		
J. Front axle:		
• 10,000 lbs. minimum capacity.		
Leaf spring suspension.		<u> </u>
• I-beam with 68" track.		
K. Rear axle:		
• 23,000 lbs. minimum capacity.	-	
Twin air spring suspension. The state of the state	-	
• Full width heavy-duty with 80" track.	+	
 Two-speed rear axle (auxiliary transmission for sweeping shall not be acceptable). 		
L. <u>Turning radius</u> :		
• 19'7" curb to curb.		
• Steering cut: 50° minimum.		
M. Brakes:		
Full air dual circuit with auto slack adjusters front and rear.		
ABS brakes.		
• Air compressor: 18.7 cfm.		
Bendix AD-9 or Authority approved equivalent air dryer.	+	
• 534Automatic moisture ejector on wet tank. (No pull chains on tanks). No Exceptions		
Parking brake alarm shall sound when brake is not set with ignition off, and		
any door opened.		
N. Frame shall be designed to accommodate sweeper unit while fully loaded with		
all accessories.		
O. Chassis shall be equipped with two (2) front tow hooks.		
CHASSIS ENGINE:		<u> </u>
A. Diesel engine shall be inline turbo-charged 6-cylinder.		
B. 500 cubic inch displacement minimum.		
C. Horsepower: 260 hp @ 2,200 rpms.		
D. Torque: 860 ft/lbs. @ 1,300 rpms.		
E. Low oil pressure and high-water temperature warning system integrated into the engine electronic system.		
F. Engine:		
Single stage dual element dry-type air cleaner.		
• Spin-on fuel filter.		
G. Clutch type drive radiator fan.		
H. Antifreeze/water mixture shall be rated to at least -34° F.		

	COMPLY	
	YES	NO
I. Fuel tank:		
• 50-gallon minimum capacity.		
• Thermostatic controlled electric fuel water separator and filter with filter		
restriction and change indicator.		
• Fuel tank shall be labeled in 1" high green letter "DIESEL FUEL ONLY".		
J. Diesel emission fluid tank: 6-gallons.		
K. Engine must meet current Federal Emission Standards.		
L. Supply a dash-mounted Diesel Particulate Filter (DPF) inhibit switch.		
M. Starter shall be a 12-volt heavy-duty with thermal over-crank protection.		
N. EPA 2024 emissions with on-board diagnostics shall be provided.		1
O. Emissions shall be CARB 2022 compliant.		
TRANSMISSION:		
A. Provide a 6-speed forward and 1-speed reverse Allison Model 3500RDS or		
Authority approved equivalent automatic transmission.		
B. Dash-mounted push button (illuminated at night) shift control.		
C. Synthetic transmission fluid shall be used and installed by OEM.		
D. Heavy-duty oil cooler and magnetic drain plugs.		
TIRES/WHEELS:		
A. Front and rear tires shall be Goodyear or Authority approved equivalent 11R x		
22.5, 14 ply highway tread radials.		
B. Front and rear steel disc wheels shall be powder coated black.		
C. Supply rear rubber (plastic shall not be acceptable) mud flaps-plain black no		
advertisements.		
CAB:		i
A. Full width aluminum cab with one-piece fiberglass tilting hood.		
B. Full power steering with dual operator controls:		
Dual OEM dash-mounted instrumentation.		
• Speedometer.		<u> </u>
• Odometer.		
• Tachometer.		
Hour meter.		
Water temperature.		
Oil pressure.		
• Voltmeter.		
Fuel gauge.		
Transmission temperature gauge.		
C. <u>Dual steering shall include:</u>		
 Right/left steering wheels. 		
Brake and throttle pedals.		_
Center mounted single windshield wiper control.		
Dual turn signal controls.		
Tilt and telescopic adjustment.		

	COMPLY	
	YES	NO
D. Console: include right/left primary driver switch, which shall change controls for		
the operator station and instrumentation from left to right and back. Switch shall only		
be able to be activated with parking brake applied.		
E. Dual high back air ride seats with orange colored 3-point seat belts with automatic		
retractors.		
F. Two (2) exterior outside heated power adjustable mirrors west coast type with 8" convex auxiliary mirrors.		
G. Hydraulic functions shall be controlled by a back lit single rocker type switch		
mounted on OEM dash activating the hydraulic power, which is supplied from the		
Hot Shift PTO on transmission. The hydraulic system shall be designed to be able to		
disengage in the event of a hydraulic oil leak.		
H. All OEM back lit rocker type switches shall be clearly labeled and mounted		
between the two (2) operator stations.		
I. Dual electric horns and dual air horns.		
J. HVAC system shall include heater, defroster, air conditioning, ventilator, and		
side window defogger.		
K. Heavy-duty rubber flooring with acoustical insulation throughout inside of cab.		
L. AM/FM/WB radio with Bluetooth and microphone, USB, front, and rear		
auxiliary inputs.		
M. Overhead console with storage and two-way radio pockets and door pockets on		
both sides.		
N. Chassis manufacture shall supply 2-way radio wiring with 20-amp fuse		
protection. Shall include 5-amp fuse and be routed to overhead radio console.		
O. Windshield wipers shall be two (2) speed plus intermittent feature with washer.		
P. Left/right grab handles for entry and exit from cab. Q. Install a Preco 45-AA or an Authority approved equivalent back-up alarm.		
R. All glass shall be tinted safety glass.		
S. Doors and ignition shall be keyed alike.		
T. Truck shall be equipped with right hand/left hand 8" stainless steel fender		
mounted convex mirrors with tripod brackets.		
U. Provide dual sun visors.		
V. Courtesy and dome lights.		
W. Door windows shall be electric open/close type.		
X. Side windows shall have a defogger.		
Y. Cab noise level while operating shall not exceed 82 dba.		
Z. It shall be the responsibility of the body builder to ensure capability of installed		
equipment with switches provided by the chassis manufacturer.		
AA. Provide in cab a dry chemical 5 lb. "UL" listed fire extinguisher suitable for		
ABC class fires mounted in a quick-release type bracket.		
BB. Triangle safety reflector shall be supplied in cab.		
CC. Cab and body lighting shall comply with all State and Federal Regulations.		
ELECTRICAL:		
A. Two (2) maintenance free 12-volt batteries, 1850 CCA.		
B. Alternator: 160-amps minimum.		

	COMPLY	
	YES	NO
C. Provide 120-volt 1,250-watt block heater with weather-proof protected flip plug		
mounted under driver's side door.		
D. All lighting shall be DOT approved including:		
Combination stop & taillights.		
Back-up lights.		
 Headlights (high beam/low beam switch). 		
 Adjustable side broom & main broom spotlights. 		
Clearance & running lights.		
Front parking & signal lights.		
Four-way flashers.		
Dome light.		
Illuminated gauges & instrument panel.		
Illuminated rocker switches.		
Self-canceling directional signals.		
Hazard switch.		
• Rotor warning light.		
E. Warning lights shall include:		
Glow plug.		
Air brakes.		
Stop & taillight failure.		
Charging system.		
Park brake.		
• Engine oil system.		
Hydraulic oil filter restriction.		
• Low spray water.		
LIGHTING:		
A. All lighting shall meet DOT safety requirements.		
B. Front and rear shall have clearance lights.		
C. Left and right sides shall have two (2) clearance lights.		
D. Front and rear directional lights with emergency flashers shall be provided.		
E. Work lights for each gutter broom and rear broom shall be provided.		
F. Dash: all console switches and all gauges shall be illuminated.		
G. An automatic back-up light with back-up alarm shall be activated when		
transmission is placed in reverse.		
H. License plate bracket shall be illuminated. I. Vehicle shall have two (2) rear side light/reflectors.		
J. A (SMV) slow moving vehicle sign shall be mounted at the rear of the broom		
sweeper.		
ROTOR WARNING LIGHT:		
A. One (1) Whelen Model R416AF or Authority approved Super-LED amber		
rotating beacon warning light with guard shall be mounted at the rear of the broom		
sweeper.		

	COMPLY	
	YES	NO
B. The Rotor Light system shall also include the following features:		
 All system wiring and switching shall be multiplex interfaced. 		
 A latched Rotor Light switch shall be green backlit and labeled Rotor Light. 		
All system functional features shall be controlled by programmable ladder logic.		
A circuit failure within the Rotor Light system layout shall flash the green on indicator in the Rotor Light switch.		
C. All wiring shall be type "SO" cord and sized to sufficiently handle current demands of all lighting.		
D. The harness wiring shall be securely mounted and routed to prevent damage, originate in the cab at the multiplex interface and terminate at each rotor light with a weatherproof socket connector. No other splicing or connections shall be acceptable.		
PAINT:		
A. All metal parts shall have the mill scale and oil removed by means of a high-pressure chemical cleaner prior to painting.		
B. Cab shall be painted manufacturers white.		
DIAGNOSTIC, REPAIR & PARTS:		
A. The awarded vendor shall provide a three (3) year manufacturers Web-based		
diagnostic, repair, and parts subscription including truck chassis and engine.		
B. Diagnostic and repair information for transmission, air-brake system, and other		
installed components shall be Web-based or PC based software.		
C. One (1) complete set of factory diagnostic and repair vehicle interface software,		
to include all necessary cabling and connections for a laptop computer or a hand-		
held device shall be supplied.	-	
MANUALS:	-	
A. A detailed schematic and description of all body hydraulics, electrical, and other components not installed by chassis manufacturer shall be provided. Two (2) of		
each of the following manuals in either paper form or computer disc shall be		
supplied upon delivery: Operation, Repair, Maintenance, Parts, and Electrical.		
WARRANTY:		
A. Engine shall be covered for a minimum of two (2) years.		
B. The transmission shall be covered for two (2) years/unlimited miles.		
C. All warranties shall start upon date of acceptance from the New Jersey Turnpike		
Authority.		
SIDE BROOMS:		
A. Broom shall be driven by a hydraulic motor directly mounted to the broom disc plate. They shall be a vertical digger design, trailing arm type mounted on right and left sides.		
B. Arm suspension shall be a parallelogram type.		
C. The broom rotation speed shall be constantly governed by a load sensing		
hydraulic system regardless of engine rpms or sweeper ground speed.		
D. Broom down pressure shall be pneumatically adjustable by the operator in the		
cab.		

2. The brooms shall have five (5) plastic segments filled with 26" long tempered wire. 3. The broom diameter shall not be less than 46" but protruding not less than 13" beyond the outside of the tire while sweeping. 3. The broom location shall be positioned to provide the best sweep path in relation of the main broom. 4. Each brooms must be capable of extending from 110" to 144" with both side prooms activated. 4. Broom shall have a spotlight for night operation. 5. Side brooms must be capable of extending from 110" to 144" with both side prooms activated. 6. Broom shall be direct drive by a hydraulic motor. 6. Broom shall be direct drive by a hydraulic motor. 7. Broom shall be tess than 34" in diameter and not less than 60" long. 7. Broom shall be full floating with self-aligning bearings. 8. Broom shall be full floating with self-aligning bearings. 8. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom side plates shall be equipped with steel drag shoes. 9. Sweeping path shall not be less than 7½" wide with one side broom activated and not less than 10" wide with both side brooms activated. 9. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). 9. Main broom and conveyor shall have at least one (1) work light each. 9. Broom shall be hydraulically raised and lowered and be capable of movement andependent of the conveyor assembly. 9. Conveyors hall be able to load hopper to 100% of rated useable capacity. 9. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in the did with cleats carrying material to hopper. Squeegec type flight system shall not be acceptable. 9. An audible conveyor stall alarm shall be provided to alert operator. 9. Conveyor shall be appable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 9. In-cab conveyor height adjustment independent of the broom height. 1. Conveyor width shall be settable independent of		COMPLY	
vire. 7. The broom diameter shall not be less than 46" but protruding not less than 13" beyond the outside of the tire while sweeping. 7. The broom location shall be positioned to provide the best sweep path in relation of the main broom. 8. Each broom shall have a spotlight for night operation. 9. Side brooms must be capable of extending from 110" to 144" with both side prooms activated. 9. MAIN BROOM: 9. A. Broom shall be direct drive by a hydraulic motor. 9. Broom shall not be less than 34" in diameter and not less than 60" long. 9. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. 9. Broom shall be full floating with self-aligning bearings. 9. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom side plates shall be equipped with steel drag shoes. 9. Sweeping path shall not be less than 7½" wide with one side broom activated and tot less than 10" wide with both side brooms activated. 9. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be exceptable). 9. Main broom and conveyor shall have at least one (1) work light each. 9. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 9. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in ultil width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 9. An audible conveyor stall alarm shall be provided to alert operator. 9. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor height adjustments to the conveyor system. 1. In-cab conveyor height adjustment independent of the main broom shall be rovided. 1. Conveyor width shall be a full 54". 1. Conveyor width shall be a time to be less than 5.4 cubic yards. Hopper inspection		YES	NO
F. The broom diameter shall not be less than 46" but protruding not less than 13" beyond the outside of the tire while sweeping. G. The broom location shall be positioned to provide the best sweep path in relation to the main broom. I. Each brooms shall have a spotlight for night operation. Side brooms must be capable of extending from 110" to 144" with both side prooms activated. MAIN BROOM: A. Broom shall be direct drive by a hydraulic motor. Broom shall be direct drive by a hydraulic motor. Broom shall be less than 34" in diameter and not less than 60" long. Broom shall be full floating with self-aligning bearings. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom side plates shall be equipped with steel drag shoes. Sweeping path shall not be less than 7½ wide with one side broom activated and not less than 10" wide with both side brooms activated. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be ecceptable). Main broom shall be shielded by a steel broom hood (plastic hoods shall not be ecceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. Conveyor shall be expable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. A. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. A. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor height shall be settable independent of the broom height. Conveyor width shal	E. The brooms shall have five (5) plastic segments filled with 26" long tempered		
peyond the outside of the tire while sweeping. 1. The broom location shall be positioned to provide the best sweep path in relation of the main broom. 2. Each broom shall have a spotlight for night operation. 3. Side brooms must be capable of extending from 110" to 144" with both side prooms activated. 2. MAIN BROOM: 3. Broom shall be direct drive by a hydraulic motor. 3. Broom shall be direct drive by a hydraulic motor. 3. Broom shall be best shan 34" in diameter and not less than 60" long. 3. Broom shall be prefab disposable type filled with 26" long polypropylene. 4. Broom shall be full floating with self-aligning bearings. 5. Broom shall be prefab disposable type filled with 26" long polypropylene. 5. Broom shall be prefab disposable type filled with 26" long polypropylene. 6. Broom shall be shall not be less than 7½'s wide with one side broom activated and not less than 10' wide with both side brooms activated. 7. Broom shall be shielded by a steel broom hood (plastic hoods shall not be exceptable). 8. Main broom and conveyor shall have at least one (1) work light each. 9. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 1. In-eab hydraulic float main broom suspension shall be provided. 2. CONVEYOR: 1. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in ull width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 2. An audible conveyor stall alarm shall be provided to alert operator. 3. Conveyor shall be eapable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 5. In-cab conveyor height adjustment independent of the main broom shall be rovided. 6. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be a full 54". 4. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 8. Volumetric capacity shall not be less than 5.4 cu	wire.		
3. The broom location shall be positioned to provide the best sweep path in relation of the main broom. 4. Each broom shall have a spotlight for night operation. 5. Side brooms must be capable of extending from 110" to 144" with both side prooms activated. 5. Broom shall be direct drive by a hydraulic motor. 6. Broom shall be direct drive by a hydraulic motor. 7. Broom shall be less than 34" in diameter and not less than 60" long. 7. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. 8. Broom shall be full floating with self-aligning bearings. 8. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom shall be prefab disposable type filled with one side broom activated and not less than 10" wide with both side brooms activated. 1. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be exceptable). 1. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 2. In-cab hydraulic float main broom suspension shall be provided. 2. CONVEYOR: 2. An audible conveyor stall alarm shall be provided to alert operator. 2. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 2. An audible conveyor stall alarm shall be provided to alert operator. 3. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 7. In-cab conveyor height adjustment independent of the main broom shall be rorovided. 3. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be a full 54". 1. HOPPER: 4. A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 8. Volumetric capacity shall not be less than 5.4 cubic y	F. The broom diameter shall not be less than 46" but protruding not less than 13"		
4. Each broom shall have a spotlight for night operation. 5. Side brooms must be capable of extending from 110" to 144" with both side brooms activated. MAIN BROOM: 6. Broom shall be direct drive by a hydraulic motor. 7. Broom shall be direct drive by a hydraulic motor. 8. Broom shall not be less than 34" in diameter and not less than 60" long. 7. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. 8. Broom shall be full floating with self-aligning bearings. 8. Broom shall be prefab disposable type filled with 26" long polypropylene. 9. Broom side plates shall be cquipped with steel drag shoes. 9. Sweeping path shall not be less than 7½ wide with one side broom activated and not less than 10' wide with both side brooms activated. 1. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). 1. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 6. In-cab hydraulic float main broom suspension shall be provided. 7. CONVEYOR: 8. Conveyor shall be able to load hopper to 100% of rated useable capacity. 8. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in ull width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 7. An audible conveyor stall alarm shall be provided to alert operator. 7. Conveyor shall be reversible in direction. The main broom shall stop rotation withile conveyor is reversed. 8. Conveyor shall be reversible in direction. The main broom shall stop rotation withile conveyor height adjustment independent of the main broom shall be provided. 8. Conveyor shall be reversible in direction. The main broom shall stop rotation withile conveyor height adjustment independent of the main broom shall be arrowided. 9. Conveyor shall be apable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 9. In-cab conv	beyond the outside of the tire while sweeping.		
H. Each broom shall have a spotlight for night operation. Side brooms must be capable of extending from 110" to 144" with both side brooms must be capable of extending from 110" to 144" with both side brooms activated. MAIN BROOM: A. Broom shall be direct drive by a hydraulic motor. B. Broom shall not be less than 34" in diameter and not less than 60" long. C. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom side plates shall be equipped with steel drag shoes. S. Sweeping path shall not be less than 7½" wide with one side broom activated and not less than 10" wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be exceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. C. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. CONVEYOR: A. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in ull width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. C. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor height adjustment independent of the main broom shall be derived to alert operator. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. C. In-cab conveyor height adjustment independent of the main broom shall be drovided. To provide proper clearance during variable sweeping conditions the minimum tenveloned. CONVER: A. Hopper	G. The broom location shall be positioned to provide the best sweep path in relation		
. Side brooms must be capable of extending from 110" to 144" with both side rooms activated. MAIN BROOM: A. Broom shall be direct drive by a hydraulic motor. B. Broom shall not be less than 34" in diameter and not less than 60" long. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom side plates shall be equipped with steel drag shoes. Seeping path shall not be less than 7½" wide with one side broom activated and not less than 10" wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement nedependent of the conveyor assembly. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in third thirt capacity. CONVEYOR: A. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. C. Conveyor shall be sepable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. The cab conveyor height adjustment independent of the main broom shall be monitored. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. To conveyor width shall be settable independent of the broom height. CONVEYOR: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. Noulmetric capacity shall not be less than 5.4 cubic yards. Hopper inspectio	to the main broom.		
AL Broom shall be direct drive by a hydraulic motor. A. Broom shall not be less than 34" in diameter and not less than 60" long. C. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom shall be prefab disposable type filled with 26" long polypropylene. Broom side plates shall be equipped with steel drag shoes. S. Sweeping path shall not be less than 7½ wide with one side broom activated and not less than 10" wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be ecceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. C. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. S. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in uill width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be roovided. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted.	H. Each broom shall have a spotlight for night operation.		
A. Broom shall be direct drive by a hydraulic motor. 3. Broom shall not be less than 34" in diameter and not less than 60" long. C. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom shall be shall not be less than 7½' wide with one side broom activated and lot less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. S. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in all width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be settable independent of the broom height. H. Conveyor width shall be settable independent of the broom height. H. Conveyor width shall be settable inde	I. Side brooms must be capable of extending from 110" to 144" with both side		
A. Broom shall be direct drive by a hydraulic motor. 3. Broom shall not be less than 34" in diameter and not less than 60" long. C. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom side plates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½" wide with one side broom activated and not less than 10" wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be monweyor height adjustment independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	brooms activated.		
3. Broom shall not be less than 34" in diameter and not less than 60" long. 2. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. 3. Broom shall be full floating with self-aligning bearings. 3. Broom shall be prefab disposable type filled with 26" long polypropylene. 5. Broom side plates shall not be less than 7½' wide with one side broom activated and not less than 10' wide with both side brooms activated. 4. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). 5. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 6. In-cab hydraulic float main broom suspension shall be provided. 7. CONVEYOR: 8. A. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in and with cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 6. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor height adjustment independent of the main broom shall be roversible in direction. The main broom shall be roversible in direction. The main broom shall be provided. 6. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 6. In-cab conveyor height adjustment independent of the main broom shall be roverided. 6. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. 8. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 8. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	MAIN BROOM:		
3. Broom shall not be less than 34" in diameter and not less than 60" long. 2. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. 3. Broom shall be full floating with self-aligning bearings. 3. Broom shall be prefab disposable type filled with 26" long polypropylene. 5. Broom side plates shall not be less than 7½' wide with one side broom activated and not less than 10' wide with both side brooms activated. 4. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). 5. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. 6. In-cab hydraulic float main broom suspension shall be provided. 7. CONVEYOR: 8. A. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in and with cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 6. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor height adjustment independent of the main broom shall be roversible in direction. The main broom shall be roversible in direction. The main broom shall be provided. 6. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 6. In-cab conveyor height adjustment independent of the main broom shall be roverided. 6. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. 8. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 8. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
C. Broom rotation speed shall be constant governed by the load sensing hydraulic system regardless of engine speed. D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. The Broom side plates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½ wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. C. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. G. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. The ab conveyor height adjustment independent of the main broom shall be provided. The provide proper clearance during variable sweeping conditions the minimum tonveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom shall be pates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½ wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement andependent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
D. Broom shall be full floating with self-aligning bearings. E. Broom shall be prefab disposable type filled with 26" long polypropylene. The Broom side plates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½" wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. S. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in hall width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
E. Broom shall be prefab disposable type filled with 26" long polypropylene. F. Broom side plates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½' wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. G. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. G. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted.			
F. Broom side plates shall be equipped with steel drag shoes. G. Sweeping path shall not be less than 7½' wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. B. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. Noulmetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
G. Sweeping path shall not be less than 7½' wide with one side broom activated and not less than 10' wide with both side brooms activated. H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
A. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
H. Main broom shall be shielded by a steel broom hood (plastic hoods shall not be acceptable). Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. C. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be brovided. B. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
Main broom and conveyor shall have at least one (1) work light each. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. Lin-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
A. Broom shall be hydraulically raised and lowered and be capable of movement independent of the conveyor assembly. K. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in will width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be brovided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
A. Conveyor shall be able to load hopper to 100% of rated useable capacity. A. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in with the cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. C. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be convided. C. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	• • • • • • • • • • • • • • • • • • • •		
C. In-cab hydraulic float main broom suspension shall be provided. CONVEYOR: A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. C. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
A. Conveyor shall be able to load hopper to 100% of rated useable capacity. 3. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
A. Conveyor shall be able to load hopper to 100% of rated useable capacity. B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	K. In-cab hydraulic float main broom suspension shall be provided.		
3. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 3. An audible conveyor stall alarm shall be provided to alert operator. 3. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. 3. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 4. In-cab conveyor height adjustment independent of the main broom shall be provided. 5. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. 5. H. Conveyor width shall be a full 54". 6. HOPPER: 6. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 6. Solumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	CONVEYOR:		
3. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in full width cleats carrying material to hopper. Squeegee type flight system shall not be acceptable. 3. An audible conveyor stall alarm shall be provided to alert operator. 3. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. 3. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. 4. In-cab conveyor height adjustment independent of the main broom shall be provided. 5. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. 5. H. Conveyor width shall be a full 54". 6. HOPPER: 6. Hopper shall have a right-side dump. All dump controls shall be cab mounted. 6. Solumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	A. Conveyor shall be able to load hopper to 100% of rated useable capacity.		
De acceptable. C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	B. Conveyor shall be designed of high-strength belt with thirteen (13) molded-in		
C. An audible conveyor stall alarm shall be provided to alert operator. D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	full width cleats carrying material to hopper. Squeegee type flight system shall not		
D. Conveyor shall be reversible in direction. The main broom shall stop rotation while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	be acceptable.		
while conveyor is reversed. E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	C. An audible conveyor stall alarm shall be provided to alert operator.		
E. Conveyor shall be capable of effectively sweeping debris of varying sizes without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be provided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	D. Conveyor shall be reversible in direction. The main broom shall stop rotation		
without the need to make any manual adjustments to the conveyor system. F. In-cab conveyor height adjustment independent of the main broom shall be brovided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	while conveyor is reversed.		
F. In-cab conveyor height adjustment independent of the main broom shall be brovided. G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	E. Conveyor shall be capable of effectively sweeping debris of varying sizes		
G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	without the need to make any manual adjustments to the conveyor system.		
G. To provide proper clearance during variable sweeping conditions the minimum conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	F. In-cab conveyor height adjustment independent of the main broom shall be		
conveyor height shall be settable independent of the broom height. H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	provided.		
H. Conveyor width shall be a full 54". HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	G. To provide proper clearance during variable sweeping conditions the minimum		
HOPPER: A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	conveyor height shall be settable independent of the broom height.		
A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	H. Conveyor width shall be a full 54".		
A. Hopper shall have a right-side dump. All dump controls shall be cab mounted. B. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection	HOPPER:		
3. Volumetric capacity shall not be less than 5.4 cubic yards. Hopper inspection			
ion man de supplieu.	door shall be supplied.		

	COMPLY	
	YES	NO
C. A hopper full indicator shall be located inside the cab in full view of the		
operator.		
D. Hopper shall be able to dump at varying heights ranging from 38" through a		
height of 11'. Dump angle shall be 50° minimum.		
E. The lift mechanism shall be a double stage design scissor lift system.		
F. The hopper shall have 11" side shift of load for maximum dumping efficiency		
and extra clearance between sweeper and dump truck. The minimum clearance		
between sweeper and truck shall be 28".		
G. Hopper shall always be visible from the cab through a glass window and		
skylight.		
H. Maximum dump cycle: 70 seconds.		
I. Lift capacity: 11,000 lbs. minimum.		
J. Hopper shall be constructed of 7-gauge abrasion resistant steel floor and 11-		
gauge door, top, and sides.		
K. Jack stands and/or outriggers to stabilize chassis during dumping shall not be		
acceptable.		
HOPPER LINER:		
A. Hopper shall be spray coated with Lifeliner or Authority approved equivalent		
coating to protect the hopper.		
B. The hopper liner design shall be extremely resistant to solvents, acids, caustics,		
and other similar chemicals.		
C. The liner shall be manufactured to be extremely smooth and slick allowing		
material not to stick to it.		
D. Warranty: hopper shall either be repaired or replaced due to corrosion or wear		
perforation during the life of the sweeper.		
WATER SYSTEM:		
A. Tank capacity: 360-gallons minimum.		
B. Tank shall be constructed of non-metallic, non-rusting polyethylene material. A		
removable manhole cover for tank access shall be provided.		
C. Water pump shall be a diaphragm type capable of running dry without damage.		
D. A water level gauge indicator shall be in the cab.		
E. Ten (10) brass spray nozzles for dust suppression, three (3) spray nozzles shall		
be over each side of broom, three (3) spray nozzles shall be located at the main		
broom.		
F. Water fill hose shall be at least 15' long equipped with 2½" NST hydrant		
coupler.		
G. Water to each area, side broom left or right, and broom spray bar shall be cab		
controlled with adjustable valves that shall control water flow.		
H. An in-line water filter with shut off valve shall be provided in the water system		
to prevent containments.		
I. Tank shall be equipped with an anti-siphon device.		
HYDRAULIC SYSTEM:		
A. Reservoir capacity: 23-gallons and include an outside level and temperature		
indicator.		
B. Twin pumps shall be a variable displacement piston type that shall be driven by		
a hot shift PTO with load sensing to adjust flow based on hydraulic oil demand.		

	COMPLY	
	YES	NO
C. Reservoir vent shall be equipped with a 40-micron breather filter.		
D. Return lines shall be equipped with a 10-micron filter with cab mounted		
restriction indicator.		
E. All pressure hydraulic fittings shall be ORFS type. All solenoids shall be in a		
single accessible location.		
F. All circuits shall have quick-disconnect check ports.		
PNEUMATIC SYSTEM:		
A. A pressure protector shall be supplied for the chassis air system for protection.		
B. All pneumatic cylinders shall be interchangeable.		
C. All pneumatic cylinders shall be rated at 150 psi and have a separate rod seal		
and wiper to prevent contamination from entering the cylinder.		
SWEEPER ELECTRICAL SYSTEM:		
A. The sweeper electrical system shall be integral to the chassis electrical system.		
B. Sweeper lighting shall include rear identification lights, side broom and rear		
clearance lights.		
C. An electronic back-up alarm shall be provided for additional safety when chassis		
is in reverse. D. Swaanan wining homogoog shall be colon and and hat stammed with singuit		
D. Sweeper wiring harnesses shall be color-coded and hot stamped with circuit		
E. All electrical circuits shall be protected by circuit breakers or fuses.		
SWEEPER CONTROLS:		
A. All sweeper controls shall be mounted on an adjustable central console located		
between the left and right operator's position for access.		
B. The controls shall include sweeping, hopper, elevator, and lighting functions and		
shall be located on the adjustable operator control console.		
C. The controls for sweeping, spraying water, and lighting functions shall be		
conventional back-lit rocker switches.		
SWEEPER INSTRUMENTS:		
A. Sweeper instruments shall include:		
Right/left side brooms down pressure.		
Hydraulic filter restriction indicator.		
Hydraulic oil temperature.		
Spray water level indicator.		
B. Oil cooler, hydraulic tank and electrical locker shall be in a protective vandal proof		
cabinet that shall open to 180° providing 270° of complete accessibility to all		
maintenance components.		
C. Rear compartment shall include a lockable stainless-steel toolbox measuring 24"		
long x 13½" wide x 63/8" tall for operator tools.		
ACCESSORIES:		
A. Front spray bar.		
B. Four (4) chassis keys.		
C. Air purge for water system.		
D. Heavy-duty lower conveyor roller.		

	COMPLY	
	YES	NO
E. Hopper full indicator.		
F. Hydrant wrench.		
G. URB strip main broom with center sweep mandrel.		
H. Piranha brooms.		
I. Rear door striping.		
J. Side body striping.		
K. Auto lube system for automatic lubrication of sweeper.		
L. Extended hopper door.		
M. Tilting of left and right-side broom shall be variable from the cab. An electrically controlled linear actuator shall allow the operator to tilt the side brooms inward and outward from the cab, while sweeping.		
PAINT:		
A. All visible exterior metallic surfaces shall be painted prior to assembly with a polyester powder coat. The paint shall be at least 2 mils thick.		
B. A. The body color paint shall be Omaha Orange, DuPont #31, or Authority approved equivalent.		
C. Vehicle shall have the paint color of grey on the lower portions of the unit.		
MANUALS:		
A. The following manuals shall be supplied for the broom sweeper for each unit ordered:		
Operation-2		
Maintenance -2		
• Parts-2		
• Engine-1		
WARRANTY:		
A. Entire sweeper shall be warranted for a period of at least two (2) years.		
B. Water tank shall be warranted for the lifetime of the sweeper.		

FAILURE TO COMPLETE ALL AREAS MAY RESULT IN REJECTION OF BID

UNIT INFORMATION FORM

(Must be submitted by vendor with bid documents)

TRUCK CHASSIS:

YEAR: MAKE:		MOI	DEL:	
ENGINE MAKE:				
MODEL:	CID:	HP:	<u></u> @	RPM
ALTERNATOR MAKE: AMPS:		MOD	EL:	
BATTERY VOLTS/AMPS: C.C.A. @ O° F:			-	
TRANSMISSION MAKE:				
MODEL:			_	
BACK-UP ALARM MAKE:				
TIRE SIZES: FRONT:		REAR:		
SERVICING AGENCY:				
ADDRESS:				
TELEPHONE #:				
CONTACT:				

Name & Title

<u>•</u>

BROOM SWEEPER: YEAR: MAKE: MODEL: ____ HOPPER SIZE: _____CUBIC YARDS SIDE BROOMS: _____DIAMETER MAIN BROOM: ____ DIAMETER SWEEPING PATH: _____FT. WIDE WATER TANK CAPACITY: _____GALLONS INSTALLER: SERVICING AGENCY: ADDRESS: TELEPHONE #: CONTACT: Name & Title **ROTOR LIGHT:** YEAR: _____ MAKE: _____ MODEL: ____ INSTALLER: SERVICING AGENCY: ____ ADDRESS: TELEPHONE #: CONTACT:

Name & Title

Exception Form: Bidders may list proposed equivalent items and should include the item number, item description, manufactu	rer's name, model number and packaging
quantities of those items which the Bidder proposes to substitute conditions, limitations, or other provisos to their bid. Please be	
other exceptions that are deemed to be a material deviation from	
cause for rejection of the bid.	is the specifications shall be a manager,
•	
Delivery Date Exception	
Warranty Date Exception	
Vendor's Name	
Signature of Vendor Responsible Officer	
Date	



NEW JERSEY TURNPIKE AUTHORITY

P.O. Box 5042 Woodbridge, New Jersey 07095 or 1 Turnpike Plaza Woodbridge, New Jersey 07095 Tel. – 732-750-5300 Fax – 732-750-5399

INSTRUCTIONS TO BIDDERS

PLEASE READ THE INSTRUCTIONS CAREFULLY BEFORE SUBMITTING YOUR BID

TABLE OF CONTENTS

Section No. Definitions						
I	Definitions			3		
II	State Laws Requiring		g Mandatory Compliance By All Bidders	3		
		A.	Division of Revenue Registration	3		
		В.	Equal Employment Opportunity Compliance	4		
		B-1	Equal Pay Reporting Requirement - Diane B. Allen Act	4		
		C.	Ownership Disclosure Form	5		
		D.	Political Contributions Compliance	5		
		E.	Prevailing Wage Act	5		
		F.	Public Works Contractor Registration Act	5		
		G.	Foreign Corporation	6		
		Н.	Small Business Enterprises	6		
		I.	Code of Ethics	6		
		J	Vendor location Disclosure	7		
		J-1	Disclosure of Investment Activities in Iran	7		
		J-2	Russia Interim Certification	7		
		K.	Set-Off for Outstanding Tax Liability	8		
		L.	MSDS Requirements	8		
		Μ.	Labeling Requirements	8		
		N.	VOC Requirements	8		
		О.	Compliance with State and Federal Laws	8		
		Р.	Safety & Health Requirements	9		
		Q.	Choice of Law	9		
III	Bid Preparat	ion				
	Dia i i cparac	A.	Bid Submission	10		
		B.	Corrections	10		
		C.	Bid Prices	10		
		D .	Payment Term	10		
		E.	Alternates	10		
IV	Riddor Cuore	antoos s	and Miscellaneous Contract Requirements			
1 4	Diduct Guara	Antees a	Warranty	11		
		А. В.	Bid Security	11		
		С .	Contract Bond	11		
		D.	Electronic Payment	11		
		Б.	Non-Collusion	12		
		12.	Non-Conusion	12		
V						
		A.	Insurance	13		
		B.	Indemnification	15		
		С.	Patent Indemnification	15		

VI	Delivery Requirements					
		A.	Delivery Date	15		
		B.	F.O.B.	15		
		C.	Delivery	16		
VII	Other Terms and Conditions					
		A.	Contract Period	16		
		B.	Extension Option	16		
		C.	Termination of Contract	16		
		D.	Scope	17		
		E.	Bidders Facilities	17		
		F.	Testing	17		
		G.	Inspection	17		
		Н.	Awards	18		
		I.	Notice To Vendors and Authority Departments	18		
		J	Right To Audit	18		
		K.	Taxes	18		
		L.	Transfer of Business	18		
		M.	Interagency Cooperative Purchasing	19		
		N.	Contract Changes	19		
		0.	Subcontracting or Assignment	19		
		P.	Rejection of Bids	19		
		Q.	Liabilities or Debts Owed to The Authority	19		
	EXHIBITS					
	211112112	A.	Mandatory Equal Employment Opportunity Language	20		
		В.	Affirmative Action Information Sheet	22		
		C.	Ownership Disclosure Form	23		
		D.	State Contractor Political Contributions Compliance	27		
			Public Law 2005, Chapter 51 & EO 117			
		E.	NJ Election Law Enforcement Commission	30		
			Requirement for Disclosure of Political Contributions			
		F.	Small/Minority/Woman Owned Business Enterprise	31		
		G.	Vendor Disclosure Form EO 129	32		
		G-1	Iran Disclosure	33		
		G-2	Russia Interim Certification	35		
		Н.	Notice to All Bidders Set-Off for State Tax	36		
		I.	Letter of Surety	37		
		J.	Proposal Bond	39		
		K.	Contract Bond	41		
		L.	Insurance Waiver	43		
		M	Instruction and Agreement for Direct Payments (ACH)	44		

INSTRUCTIONS TO BIDDERS FOR SUBMISSION OF BIDS STANDARD TERMS AND CONDITIONS

The following Standard Terms and Conditions apply to all contracts, purchase agreements or purchase orders with the New Jersey Turnpike Authority unless specifically stated otherwise in the Invitation to Bid/Request for Bids ("RFB"). Bidders are hereby notified that all Terms and Conditions contained herein will become a part of any contract(s) awarded or order(s) placed as a result of any RFB fully and to the same extent as if copied at length therein. In the case of a conflict between these general Terms and Conditions and the specific provisions of the RFB, the RFB shall control. Failure to comply with each and every one of the below Terms and Conditions, as well as the specific requirements set forth in the RFB, may be grounds for rejection of the bid.

I. <u>DEFINITIONS</u>

The following definitions will be a part of any RFB issued by the New Jersey Turnpike Authority, and any contract(s) awarded or order(s) placed as a result of such documents.

- a. "Authority" shall mean the New Jersey Turnpike Authority.
- b. "Bidder" shall mean any potential vendor submitting a response to an RFB issued by the Authority.
- c. "Contract" shall mean the RFB (including these Standard Terms and Conditions), the response thereto submitted by the bidder, and the Authority's Notice of Award.
- d. "Director" shall mean the Director of Procurement & Materials Management Department of the Authority.
- e. "Vendor" shall mean the successful bidder who is awarded the contract at issue.

II. STATE LAWS REQUIRING MANDATORY COMPLIANCE BY ALL BIDDERS

A. DIVISION OF REVENUE REGISTRATION-Pursuant to the terms of *N.J.S.A.* 52:32-44, bidders are required to submit to the Authority proof of valid business registration with the New Jersey Division of Revenue in the Department of Treasury, prior to entering into a contract with the Authority. No contract shall be entered into by the Authority unless the bidder first provides proof of valid business registration. In addition, bidders are required to provide to the Authority proof of valid business registration with the Division of Revenue for any and all subcontractors that will be used to provide goods or services under the contract. A copy of the bidder's and any subcontractor's valid Certificate of Registration should be included with the bid submission and must be in effect prior to the contract award.

All questions regarding this requirement should be referred to the Division of Revenue hotline at (609)-292-9292 or/online: http://www.nj.gov/treasury/revenue/forms/njreg.pdf

- **B. EQUAL EMPLOYMENT OPPORTUNITY COMPLIANCE** Bidders must agree not to discriminate in employment and are required to comply with all applicable anti-discrimination laws, including those contained within *N.J.S.A.* 10:2-1 through 10:2-4, *N.J.S.A.* 10:5-1, et seq., and *N.J.S.A.* 10:5-31, et seq., <u>P.L.</u> 1975, <u>c.</u> 127. The mandatory language required by <u>P.L.</u> 1975, <u>c.</u> 127, as set forth in Exhibit A, shall be deemed a material term of any and all contracts, purchase agreements, and purchase orders entered into by the Authority. Bidders must acknowledge their agreement with the terms set forth in Exhibit A by signing where indicated and returning the exhibit with the bid. In addition, Bidders must affirmatively demonstrate compliance with <u>P.L.</u> 1975, <u>c.</u> 127 by submitting with the bid the completed Affirmative Action Information Sheet, set forth in Exhibit B, and any required attachments.
 - 1) Anti-discrimination provision required by *N.J.S.A.* 10:2-1 In the hiring of persons for the performance of work under this contract or any subcontract hereunder, or for the procurement, manufacture, assembling or furnishing of any such materials, equipment, supplies or services to be acquired under this contract, no contractor, nor any person acting on behalf of such contractor or subcontractor, shall, by reason of race, creed, color, national origin, ancestry, marital status, gender identity or expression, affectional or sexual orientation or sex, discriminate against any person who is qualified and available to perform the work to which the employment relates.
 - 2) No contractor, subcontractor, nor any person on his behalf shall, in any manner, discriminate against or intimidate any employee engaged in the performance of work under this contract or any subcontract hereunder, or engaged in the procurement, manufacture, assembling or furnishing of any such materials, equipment, supplies or services to be acquired under such contract, on account of race, creed, color, national origin, ancestry, marital status, gender identity or expression, affectional or sexual orientation or sex.
 - 3) There may be deducted from the amount payable to the contractor by the contracting public agency, under this contract, a penalty of \$ 50.00 for each person for each calendar day during which such person is discriminated against or intimidated in violation of the provisions of the contract; and
 - 4) This contract may be canceled or terminated by the contracting public agency, and all money due or to become due hereunder may be forfeited, for any violation of this section of the contract occurring after notice to the contractor from the contracting public agency of any prior violation of this section of the contract.

B-1 Equal Pay Reporting Requirement Pursuant to N.J.S.A. 34:11-56.1 et seq.

Pursuant to the Diane B. Allen Equal Pay Act (N.J.S.A. 34:11-56.1 et seq.), any employer, regardless of the location of the employer, that enters into a contract with the Authority to provide any service that is not a public work as defined by N.J.S.A. 34:11-56.25 (5) must file annual Equal Pay Reports with the New Jersey Commissioner of Labor and Workforce Development, including information regarding the compensation and hours worked by employees categorized by gender, race, ethnicity and job category. Forms and instructions for Equal Pay Reports have been adopted for services contractors, which forms must be filed annually by March 31 for the preceding year, using employment figures from any period in October through December. See https://nj.gov/labor/equalpay.html.

- C. OWNERSHIP DISCLOSURE FORM-Bidders who are corporations, partnerships or limited liability companies must comply with <u>P.L.</u> 1977, <u>c.</u> 33, *N.J.S.A.* 52:25-24.2, by completing the Ownership Disclosure Form, set forth in Exhibit C, and submitting it with the bid. Failure to do so shall result in rejection of the bid.
- **D. POLITICAL CONTRIBUTIONS COMPLIANCE-**To be eligible for an award, bidders must comply with the requirements of <u>P.L.</u> 2005, <u>c.</u> 51, *N.J.S.A* 19:44 A-20.13 et seq., and with the requirements of Executive Order 117 (Corzine). No award may be made to a bidder who has not complied with these laws regarding political contributions. A more detailed explanation of these requirements is set forth in Exhibit D.

1. ADDITIONAL DISCLOSURE REQUIREMENTS OF P.L. 2005, C. 271

Bidders are advised of their responsibility to file annual disclosure statements on political contributions with the New Jersey Election Law Enforcement Commission (ELEC), pursuant to <u>P.L.</u> 2005, <u>c.</u> 271, section 3, if they receive contracts in excess of \$50,000 from any public entity in a calendar year. It is the bidder's responsibility to determine if filing is necessary. Failure to so file can result in the imposition of financial penalties by ELEC. Bidders must include with their bid a statement acknowledging this requirement, on the form set forth in Exhibit E. Additional information about this requirement is available from ELEC at 888-313-3532 or at www.elec.state.nj.us.

- **E. PREVAILING WAGE ACT**-The New Jersey Prevailing Wage Act, *N.J.S.A.* 34:11-56.26 et seq., is hereby made a part of every contract entered into on behalf of the Authority, except those contracts which are not within the contemplation of the Act. The bidder's signature on its bid is its guarantee that neither it nor any subcontractors it might employ to perform the work covered by the contract has been suspended or debarred by the New Jersey Department of Labor and Workforce Development for violation of the provisions of the Prevailing Wage Act and/or the Public Works Contractor Registration Act. The bidder's signature on its bid is its guarantee that both it and any subcontractors it might employ to perform the work covered by the contract will comply with the provisions of the Prevailing Wage and Public Works Contractor Registration Acts, where required.
- F. PUBLIC WORKS CONTRACTOR REGISTRATION ACT-The New Jersey Public Works Contractor Registration Act requires all contractors, subcontractors and lower tier subcontractors who bid on or engage in any contract for "public work," as defined in *N.J.S.A.* 34:11-56.51, to be first registered with the Department of Labor and Workforce Development. No vendor or subcontractor, including lower tier subcontractors, shall engage in the performance of any public work subject to the contract unless they are registered pursuant to this Act. Bidders can submit a valid copy of their Public Works Contractor Registration Certificate and valid copies of the Registration Certificates for all subcontractors along with the bid, but the certificate(s) must be submitted prior to contract award. The Registration Certificate(s) shall be maintained at the worksite and shall be made readily available for inspection at any time. Pursuant to *N.J.S.A.* 34:11-56.55 applications for registration shall not be accepted as a substitute for a Registration Certificate for subcontractors.

Any questions regarding this requirement should be directed to the Division of Wage and Hour Compliance, Department of Labor and Workforce Development at (609) 292-9464.

G. FOREIGN CORPORATION-If applicable, the bidder shall register as a "Foreign Corporation" with the Secretary of the State of New Jersey, designating a resident agent for the service of process. Foreign corporations must obtain a certificate of authority to do business in NJ pursuant to *N.J.S.A.* 14A:13-3. Written proof of such registration must be included with the bid submission.

H. SMALL BUSINESS ENTERPRISE SET-ASIDE CONTRACT FOR GOODS AND SERVICES It is the policy of the Authority that small business enterprises ("SBE") as determined and defined by the State of New Jersey, Division of Revenue and Enterprise Services ("Division") in the Department of the Treasury (*N.J.A.C.*17:13-1.2) have the opportunity to compete for and participate in the performance of contracts and subcontract for construction and for the purchase of goods and services. The Authority further requires that its contractors/vendors agree to take all necessary and responsible steps, in accordance with *N.J.S.A.* 52:32-17 et seq. and *N.J.A.C.* 17:13-1 et seq. to ensure that SBE's have these opportunities, as an aid in meeting the commitment of its SBE Programs. When applicable the Authority will designate the contract as a SBE Set-Aside Contract. In such cases requests for bid proposals shall be confined to businesses registered with the Division as an SBE in either Category 1, 2, or 3. Bid proposals from businesses not designated as an SBE, when applicable, will be rejected.

- I. CODE OF ETHICS: Bidders are advised that the Authority has adopted the New Jersey Uniform Code of Ethics, a copy of which can be viewed by going to the following web site: http://nj.gov/ethics/docs/ethics/uniformcode.pdf By submitting a bid, bidders agree to be subject to the intent and purpose of said Code and to the requirements of the New Jersey State Ethics Commission.
 - 1) No vendor shall pay, offer to pay, or agree to pay, either directly or indirectly, any fee, commission, compensation, gift, gratuity, or other thing of value of any kind to any State officer or employee or special State officer or employee, as defined by *N.J.S.A.* 52:13D-13b. and e., in the Department of the Treasury or any other agency with which such vendor transacts or offers or proposes to transact business, or to any member of the immediate family, as defined by *N.J.S.A.* 52:13D-13i., of any such officer or employee, or any partnership, firm, or corporation with which they are employed or associated, or in which such officer or employee has an interest within the meaning of *N.J.S.A.* 52:13D-13g.
 - 2) The solicitation of any fee, commission, compensation, gift, gratuity or other thing of value by any State officer or employee or special State officer or employee from any State vendor shall be reported in writing forthwith by the vendor to the Attorney General and the Executive Commission on Ethical Standards.
 - 3) No vendor may, directly or indirectly, undertake any private business, commercial or entrepreneurial relationship with, whether or not pursuant to employment, contract or other agreement, express or implied, or sell any interest in such vendor to, any State officer or employee or special State officer or employee having any duties or responsibilities in connection with the purchase, acquisition or sale of any property or services by or to any State agency or any instrumentality thereof, or with any person, firm or entity with which he is employed or associated or in

- which he has an interest within the meaning of *N.J.S.A.* 52:13D-13g. Any relationships subject to this provision shall be reported in writing forthwith to the Executive Commission on Ethical Standards, which may grant a waiver of this restriction upon application of the State officer or employee or special State officer or employee upon a finding that the present or proposed relationship does not present the potential, actuality or appearance of a conflict of interest.
- 4) No vendor shall influence, or attempt to influence or cause to be influenced, any State officer or employee or special State officer or employee in his official capacity in any manner which might tend to impair the objectivity or independence of judgment of said officer or employee.
- 5) No vendor shall cause or influence, or attempt to cause or influence, any State officer or employee or special State officer or employee to use, or attempt to use, his official position to secure unwarranted privileges or advantages for the vendor or any other person.
- 6) The provisions cited shall not be construed to prohibit a State officer or employee or special State officer or employee from receiving gifts from or contracting with vendors under the same terms and conditions as are offered or made available to members of the general public subject to any guidelines the Executive Commission on Ethical Standards may promulgate as stated above.
- **J. VENDOR LOCATION DISCLOSURE-**Pursuant to *N.J.S.A.* 52:34-13.2, every contract entered into by the Authority primarily for the performance of services shall specify that all services performed under the contract or performed under any subcontract awarded under the contract shall be performed within the United States. The statute requires all bidders to disclose the origin and location of the performance of their services, including any subcontracted services that are the subject matter of the contract. Bidders must include with their bid a completed Vendor Disclosure Form, attached hereto as Exhibit G.
- **J-1 DISCLOSURE OF INVESTMENT ACTIVITIES IN IRAN-** Pursuant to *N.J.S.A.* 52:32-58, the bidder must certify that neither the bidder, nor one of its parents, subsidiaries, and/or affiliates (as defined in *N.J.S.A.* 52:32-56(e)(3)), is listed on the Department of the Treasury's List of Persons or Entities Engaging in Prohibited Investment Activities in Iran and that neither is involved in any of the investment activities set forth in *N.J.S.A.* 52:32-56(f). If the bidder is unable to so certify, the bidder shall provide a detailed and precise description of such activities. Bidders must include with their bid a completed Disclosure of Investment Activities in Iran, attached hereto as Exhibit G-1.
- J-2 RUSSIA INTERIM CERTIFCATION Prior to the time a contract is awarded, pursuant to P.L.2022, c.3, the successful Bidder must certify that neither the successful Bidder, nor one of its parents, subsidiaries, or affiliates may have engaged in prohibited activities in Russia or Belarus. If the successful Bidder is unable to so certify, the Bidder shall provide a detailed and precise description of such activities to the Authority. Failure to provide such description will result in the Proposal being rendered as non-responsive, and the Authority will not be permitted to contract with such person or entity, and if a Proposal is accepted or contract is entered into

without delivery of the certification, appropriate penalties, fines and/or sanctions will be assessed as provided by law.

If the Bidder certifies that the Bidder is engaged in activities prohibited by P.L. 2022, c. 3, the Bidder shall have 90 days to cease engaging in any prohibited activities and on or before the 90th day after this certification, shall provide an updated certification. If the Bidder does not provide the updated certification or at that time cannot certify on behalf of the entity that it is not engaged in prohibited activities, the State shall not award the business entity any contracts, renew any contracts, and shall be required to terminate any contract(s) the business entity holds with the State that were issued on or after the effective date of P.L. 2022, c. 3.

The Authority requests that all Bidders submit a copy of the form entitled "Certification of Non-involvement in Prohibited Activities in Russia or Belarus Pursuant to P.L.2022, c.3" with their Proposal. Bidders must include with their bid a completed Certification of Non-Involvement in Activities in Russia, attached hereto as Exhibit J-2.

- K. SET-OFF FOR OUTSTANDING TAX LIABILITY-Bidders are advised that pursuant to P.L. 1995, c. 159, effective January 1, 1996, and notwithstanding any provision of the law to the contrary, the State of New Jersey has the right to set-off any tax indebtedness from payments made under contracts with the Authority. The State's rights are explained in more detail in Exhibit H, attached. Bidders must provide a copy of Exhibit H acknowledging that they have received notice of the State's right of set-off prior to contract award.
- **L. MSDS REQUIREMENTS**-Any vendor, Vendor, or subcontractor who provides the Authority materials in the form of a single chemical substance or a mixture containing two or more chemical substances, or who delivers to or stores such materials at an Authority facility, must provide the Authority with a clear, legible copy of the manufacturer's most recent Material Safety Data Sheet (MSDS) for each and every one of those materials, pursuant to *N.J.A.C.* 8:59-2.2(i).
- **M. LABELING REQUIREMENTS**-Any vendor, Vendor or subcontractor who provides the Authority materials which fall under the purview of the New Jersey Worker and Community Right-to-Know-Act, *N.J.S.A.* 34:5A-1 et seq., or who stores any such materials at an Authority facility, shall ensure that each and every container of those materials is labeled in accordance with the Act and its regulations.
- **N. VOC REQUIREMENTS-**Any architectural coating, as defined by *N.J.A.C.* 7:27-23.2, provided to the Authority for its use or used and applied by any vendor or subcontractor in conjunction with an Authority project must comply with each and every requirement of the New Jersey Department of Environmental Protection's Volatile Organic Compounds in Consumer Products (VCC) regulation, *N.J.A.C.* 7:27-23.1 et seq.
- O. COMPLIANCE WITH STATE AND FEDERAL LAWS-The vendor must comply with all local, state and federal laws, rules and regulations applicable to the contract at issue and to the work to be done thereunder.

- P. SAFETY & HEALTH REQUIREMENTS-The goods, services and/or equipment provided through the contract at issue shall be so designed and installed to meet all applicable federal and state safety and health regulations and national consensus standards including, but not limited to US DOL-OSHA, NJ LWD-PEOSHA, NFPA and ANSI standards
- **Q. CHOICE OF LAW**-It is agreed and understood that any contract entered into and/or purchase orders placed as a result of any RFB issued by the Authority shall be governed and construed and the rights and obligations of the parties thereto shall be determined in accordance with the laws of the STATE OF NEW JERSEY.

III. <u>BID PREPARATION</u>

A. BID SUBMISSION-Unless the Authority has made provision for bids to be submitted online, bids must be submitted in paper format, in ink or typewritten. If space is provided on the RFB for bid details, bids must be submitted using that document. Paper bids must be signed and returned in a sealed envelope addressed to the New Jersey Turnpike Authority with the bid opening date, time and bid identification on the outside of the envelope. Bidders shall state on such form a unit price for each item and extend such unit price by multiplying same by the indicated quantities on the bids solicited by the Authority.

All bids must be received in the Authority's Purchasing Department on or before the date and time specified on the RFB. Bids received after the time indicated shall be rejected and returned to the bidder(s) unopened after being processed in accordance with established Authority procedures. The Authority will not be responsible for late postal or delivery service.

- **B. CORRECTIONS**-Any correction of an entry made on the bid should be initialed by a duly authorized representative of the bidder. If the total price is found to be incorrectly computed, discrepancies will be corrected by the Authority on the basis of the written unit prices, and determination of the low bidder will be made on the basis of the correct total price so determined.
- **C. BID PRICES-**All prices quoted shall be firm and not subject to increase during the term of the contract, unless otherwise specified in the RFB. Prices shall include transportation and delivery to the site designated by the Authority in the RFB. All delivery charges shall be borne by the vendor.
- **D. PAYMENT TERMS**-The bidder shall state the terms, if any, requested for the Authority to make payment within a certain period of time after receipt of the bidder's invoice.
- **E. ALTERNATES**-All items are to be quoted as specified in the RFB or as an approved equivalent. In those cases when an alternate product is offered, it is the bidder's responsibility to provide detailed specifications, brand, make and model of the alternate offered, in the bidder's response/bid submission. In the event a bidder fails to take exception to the published bid specifications, the Authority shall evaluate the bid as offering the specified product/service. The Authority shall determine, at its sole discretion, if any alternate product offered is acceptable as an approved equivalent.

In the event the Authority specifies a model number or item that has been replaced/superseded by another model number or item, the bidder may quote the replacement item as an alternate. In this case, the bidder must specify the manufacturer and model number of the replacement item on the response/bid submission and must supply detailed descriptive literature and/or prints with that submission. The Authority will evaluate the proposed item to determine, in its sole discretion, whether it is an approved equivalent.

IV. BIDDER GUARANTEES AND MISCELLANEOUS CONTRACT REQUIREMENTS

A. WARRANTY-The bidder hereby represents and warrants that the equipment offered is standard new equipment, latest model of regular stock product, with parts regularly used for the type of equipment offered, that such parts are all in production and none likely to be discontinued; also, that no attachment or part has been substituted or applied contrary to manufacturer's recommendations and standard practice.

The bidder shall unconditionally guarantee all new equipment for a term of one year from time of acceptance by the Authority unless specified otherwise in the RFB and shall render prompt service of such equipment without charge, regardless of geographic location. The bidder shall maintain sufficient quantities of parts necessary for proper service to equipment at distribution points and service headquarters.

- **B. BID SECURITY-**Bidder shall submit with its bid proposal, fully executed by its bonding company and itself, either: (1) the standard form Authority Letter of Surety (attached hereto as Exhibit I), or (2) the standard form Authority Proposal Bond (attached hereto as Exhibit J), in the amount of 10% of its bid price. In lieu of the Letter of Surety or Proposal Bond, the bidder may elect to furnish with its bid proposal a <u>Cashier's check</u> in the amount of 10% of the bid price as a performance warranty deposit. This bid surety will be held by the Authority until award of the contract to ensure compliance by the successful bidder with the terms and obligations of the bid including, but not limited to, delivery date.
- C. CONTRACT BOND-The vendor shall, within ten (10) calendar days of receipt of the Notice of Award, furnish and deliver the Contract Bond on the standard form of the Authority, attached hereto as Exhibit K. The Contract Bond shall be in a sum of up to 100% of the total amount bid for the contract, as specified in the RFB, and shall be maintained by the vendor until final payment is made. In the event of insolvency of the Surety, the vendor shall forthwith furnish and maintain other Surety satisfactory to the Authority.
- D. ELECTRONIC PAYMENT With the award of this contract, the successful vendor(s) will be required to receive their payment(s) electronically and invoices should be emailed to; invoicefb@njta.com In order to receive your payments via automatic deposit from the Authority, complete and return the "Authorization Agreement for Direct Payments (ACH Credits)" Form with an original voided check or bank letter. The form must include ABA number (routing or transit number), bank account number and if the bank account is a checking or savings account. The form and instructions are located in the Instruction to Bidders on the Authority's website http://www.state.nj.us/turnpike/purchasing.html. The completed form along with the required voided check or bank letter should be emailed to achvendor@njta.com

E. NON-COLLUSION-. The bidder's signature on its bid is its guarantee that said bidder has not, directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free, competitive bidding in connection with the referenced contract; and that all statements contained in the bid and any additional statements requested by the Authority are true and correct, and made with full knowledge that the Authority relies upon the truth of the statements contained therein in awarding the contract.

The bidder's signature on its bid is its guarantee, in accordance with *N.J.S.A.* 52:34-15, that no person or selling agency has been employed or retained to solicit or secure such contract upon an agreement or understanding for a commission, percentage, brokerage or contingent fee, except bona fide employees or bona fide established commercial or selling agencies maintained by the bidder for the purpose of securing business.

V. INSURANCE AND INDEMNIFICATION

A. INSURANCE-The bidder shall procure and maintain at its own expense for the entire term of the contract insurance for liability for damages imposed by law and assumed under this contract, of the kinds and in the amounts hereinafter provided. All insurance companies used must be authorized to do business in the State of New Jersey and must carry an A.M. Best Rating of A-/VII or better. Before commencing any services hereunder, the bidder shall furnish to the Authority a certificate(s) of insurance. The Authority reserves the right to request and obtain complete copies of all insurance policies showing that it has complied with this Section. All certificate(s) and notices of cancellation or change shall be mailed to: Director, Purchasing Department, New Jersey Turnpike Authority, P.O. Box 5042, Woodbridge, New Jersey 07095. Upon request, the bidder shall furnish the Authority with a certified copy of each policy itself, including the provision establishing premiums.

The type and minimum limits of insurance shall be:

1. <u>Commercial General Liability Insurance.</u> The minimum limits of liability for this insurance per accident shall be as follows:

•	Bodily injury and property damage each occurrence	\$2,000,000.00
•	Personal injury each occurrence	\$2,000,000.00
•	General Aggregate	\$2,000,000.00
•	Products and Completed Operations Aggregate	\$2,000,000.00
•	Fire Damage Legal Liability	\$100,000.00
•	Medical Payments	\$5,000.00

The above required Commercial General Liability Insurance shall name the Authority, its Commissioners, officers, employees, and agents as additional insureds. The coverage to be provided under this policy shall be provided on the ISO CG 00 01 Form or its equivalent. The insurance policy shall be endorsed to include Personal Injury, Broad Form Property Damage, Contractual Liability (including the deletion of the coverage restriction related to work conducted within fifty (50) feet of a railroad), Products/Completed Operations, Independent Consultants and XCU if applicable. Products/Completed Operations coverage shall remain in force for a period of two (2) years following the completion and/or termination of the contract.

2. **Business Automobile Liability Insurance.** The Comprehensive Automobile Liability policy shall cover owned, non-owned, and hired vehicles with minimum limits as follows:

Combined Single Limit of Liability for Bodily Injury or Property Damage for any one accident: \$2,000,000. This policy shall include an endorsement amending the Contractual Liability coverage to delete the exclusion for work done within fifty feet of the railroad, an MCS 90 as required by law and the ISO CA 99 48.

This policy shall name the Authority, its Commissioners, officers, employees, and agents as additional insured.

3. Workers Compensation and Employers' Liability Insurance. Workers Compensation Insurance shall be provided in accordance with the requirements of the laws of the State of New Jersey and shall include an All-States endorsement or similar statement in the policy declarations, extending coverage to any state which may be interpreted to have legal jurisdiction. Employers' Liability Insurance shall be provided with a limit of liability of not less than \$1,000,000 for each accident.

4. <u>Umbrella Liability Insurance.</u>

Umbrella liability insurance is required with limits **in excess** of those underlying policies stated under parts (a) Commercial General Liability, (b) Commercial Automobile Liability and (c) Employers' Liability with minimum limits as follows:

Minimum limit each occurrence and annual aggregate.....\$3,000,000 Limits can be achieved in any combination of primary and excess limits.

This policy shall name the Authority, its officers, employees, and agents as additional insured.

5. <u>Certificate and Endorsement Requirements</u>

Each of the above required policies shall contain the endorsements as stated below:

- (a) Sixty (60) days' notice of cancellation or any restriction in coverage by registered mail to the Authority.
- (b) All policies, except Workers Compensation and Employers' Liability Insurance, shall contain a waiver of subrogation clause in favor of the Authority.
- (c) With respect to the Workers' Compensation and Employers' Liability, this policy shall contain a waiver of subrogation in favor of the Authority, where allowed by law.
- (d) With respect to Commercial General Liability and Automobile Liability policies, the other insurance clause under each policy shall be amended to read as follows: "This policy will act as primary insurance and not contribute with policies issued to the Authority."

The vendor shall also require that all of its contracting parties comply with the insurance requirements stated above including providing evidence of such insurance coverages in the same manner as stated above.

<u>Due to future changes in economic financial and/or insurance market conditions the</u> Authority at its discretion may modify the above stated insurance requirements.

NOTWITHSTANDING THAT MINIMUM AMOUNTS OF INSURANCE COVERAGE CARRIED OR REQUIRED TO BE CARRIED BY THE BIDDER ARE SPECIFIED HEREIN, THE LIABILITY OF THE BIDDER SHALL NOT BE LIMITED TO THE AMOUNTS SO SPECIFIED AND SHALL EXTEND TO ANY AND ALL LIABILITY IN EXCESS OF THE INSURANCE COVERAGES SO PROVIDED NOR SHALL THESE MINIMUM LIMITS PRECLUDE THE AUTHORITY FROM TAKING ANY ACTION AVAILABLE TO IT UNDER THE PROVISIONS OF THE CONTRACT OR OTHERWISE IN LAW.

- В. INDEMNIFICATION-Vendor agrees to defend, indemnify and save harmless the Authority, its Commissioners, officers, employees, and agents and each and every one of them against and from all liabilities, judgments, threatened, pending or completed actions, suits, demands for damages or costs of every kind and description actually and reasonably incurred (including attorney's fees and costs and court costs) (collectively "Liabilities") including, without implied limitations, Liabilities for damage to property or Liabilities for injury or death of the officers, agents and employees of either the vendor or the Authority, resulting from any act or omission or willful misconduct of the vendor or any of its officers, agents, sub-consultants, or employees in any manner related to the subject matter of the contract. In the event that the vendor fails to defend, indemnify and save harmless the Authority, its Commissioners, officers, employees, and agents, and each and every one of them, in accordance with this Section, any money due to the vendor under and by virtue of the contract as shall be considered necessary by the Authority may be retained by the Authority and held until any and all liabilities shall have been settled and suitable evidence to that effect furnished to the Authority. The obligations in this Section shall survive the termination, expiration or rescission of the contract.
- C. PATENT INDEMNIFICATION-The vendor hereby agrees that it will indemnify, defend, and save harmless the Authority, its Commissioners, officers, agents and servants from all suits, actions, claims and judgments of any kind or character whatsoever for infringement of patent, trademark or copyright regarding the items bid herein that may be brought by any person, corporation, or firm.

VI. DELIVERY REQUIREMENTS

- **A. DELIVERY DATE-**A FIRM delivery date must be stated on the bid. Statements such as "stock" or "immediate" are not acceptable. Where the RFB calls for delivery within a specified time, it shall be indicated in the bid whether delivery will be made within the time specified.
- **B.** F.O.B.-Price shall include delivery to the Authority F.O.B. destination, freight paid to any destination on the New Jersey Turnpike or Garden State Parkway. No additional charge will be allowed for any transportation cost resulting from partial shipments made at vendor's convenience when a single shipment is ordered. Prices quoted are firm throughout the term of the contract for complete delivery of quantities specified.

Bids submitted on an F.O.B. destination basis are mandatory; however, in instances where customs of the trade or unusual circumstances dictate F.O.B. shipping point, an estimate of the shipping charges must be noted on the bid and may be accepted in the Director's sole discretion. In such cases, actual shipping charges are to be prepaid and added to the invoice.

C. DELIVERY-Upon award of the contract:

- 1. Deliveries shall be made at such time and in such quantities as ordered in strict accordance with conditions stated in the RFB.
- 2. Deliveries may be set on a scheduled basis as arranged between the Authority and the vendor. It shall be the responsibility of the vendor to maintain an adequate supply stock.
- 3. The vendor will be responsible, at the point of delivery, for the delivery of material in such quality and condition as required by Paragraph IV.A. hereof and in accordance with good commercial practice.
- 4. Items delivered must be strictly in accordance with those bid upon.
- 5. As applicable, bidders must state in the space provided on the RFB/bid solicitation documents the number of days required to make delivery after notification to ship.
- 6. In the event delivery is not made within the number of days stipulated, the Authority may purchase the required material from any available source. The difference in price, if any, will be paid by the vendor failing to meet its commitments.

VII. OTHER TERMS AND CONDITIONS

- A. CONTRACT PERIOD- Except as otherwise stated in the RFB, the term of the contract shall be for one (1) year, with the option to extend for two (2) one-year options, at the Authority's discretion, and with vendor's concurrence.
- **B. EXTENSION OPTION-**If, in the opinion of the Director, it is in the best interest of the Authority to extend any contract beyond the original term, for a period of all or any part of a year, the vendor will be so notified of the Director's intent, prior to the expiration date of the existing contract. The Authority reserves the right to make up to two extensions of this contract for not more than one year each. If the extension is acceptable to the Authority at the original prices and on the original terms, notice will be given to the vendor by the Director in writing. If the original contract required a Contract Bond, a new Contract Bond must be submitted to cover the period of the extension. The same insurance requirements will be required for each extension period.
- C. TERMINATION OF CONTRACT-The contract awarded may be terminated by the Authority at any time for inadequate or improper performance, or for breach of any terms, conditions, or obligations of the contract by the vendor, as determined by the Authority, or if the vendor shall make an assignment for the benefit of creditors, or file a voluntary petition in bankruptcy, or if an involuntary petition in bankruptcy is filed against the vendor and the act of bankruptcy therein alleged is not denied by the vendor, or if denied, is found by a court or jury. Further, the Authority reserves the right to terminate any contract for any reason provided written notice has been given by the Director to the vendor at least thirty (30) days prior to such proposed termination date.

The notice of termination shall be in writing and shall be effective upon receipt by the vendor. Upon termination, the Authority shall be liable only for payment for goods or services properly delivered or performed in accordance with the contract. The Authority shall have the right to purchase non-delivered goods, to replace defective goods or services on the open market and hold the vendor liable for the difference between the price set forth in the contract for such goods or services and the prices paid on the open market or pursue any other right available by law. In addition, the Authority shall have the right, without the necessity of court proceedings, to recover all equipment, material or supplies that are the property of the Authority and have been entrusted with the vendor to be used in the performance of said contract. Nothing in this paragraph is intended to limit the Authority's right to legally pursue all costs which exceed the amount due and owing the vendor under said contract. The list of remedies in this paragraph is not exclusive.

- **D. SCOPE-**The total quantities of any contract are estimated. There is no guarantee of any minimum quantity. It is understood and agreed that contract prices shall cover the quantities actually required and ordered by the Authority during the term of the contract, whether more or less than the approximate quantity stated.
- **E. BIDDERS FACILITIES**-The Authority reserves the right to inspect the bidder's establishment before making an award.
- **F. TESTING**-The Authority reserves the right to have the material tested prior to the award and during the contract by an independent testing laboratory, to determine if the material meets the specifications of the RFB. If required for testing purposes, the low bidder shall submit a reasonable quantity of the product as samples. If these samples prove satisfactory, the contract shall be awarded. If they do not prove satisfactory, a test shall be made of the next low bidder's sample, until satisfactory products are found to meet requirements. Should the laboratory find that any shipment does not meet specifications, the Authority shall have the right to reject same.
- **G. INSPECTION** All work done and supplies furnished shall be subject to inspection, testing and rejection by the Authority, or its representatives, at all times and places, both during manufacture and at destination. After award of the contract, should the result of any test or inspections show that the material supplied fails to meet the requirements of the Authority, the material shall be rejected and immediately replaced by the vendor. Rejected supplies or materials will be returned at the vendor's risk, and all inspection, handling, and transportation charges to and from the Authority's delivery site will be assumed by the vendor. The vendor shall bear any and all expenses resulting from delay caused by failure to meet test or inspection standards. Should the Authority for any reason decide to accept any shipment which fails to meet specifications, the Authority may make an appropriate price adjustment with regard to same.

- **H. AWARDS**-Comparison of bids will be based on the total price stated in the bid and an award will be based on the total price, terms and delivery date given by the bidder. If the total price is found to have been incorrectly computed, discrepancies will be corrected by the Authority on the basis of the unit prices and a determination of the low bidder will be made on the basis of the corrected total price. The Authority shall not be liable for any failure on its part to detect or correct errors, and the Authority's action in connection therewith shall not give rise to any rights to the bidder.
- I. NOTICE TO VENDORS AND AUTHORITY DEPARTMENTS-The Authority is authorized to order, and vendors are authorized to ship only those items covered by the contract. If a review of orders placed by the Authority reveals that material other than that covered by the contract has been ordered and delivered, the Director will take such steps as are necessary to have the material returned regardless of the time elapsed between the date of delivery and discovery of the violation. A full refund to the Authority by the vendor will be required.
- **RIGHT TO AUDIT-**Vendor shall keep and maintain proper and adequate books, records and accounts accurately reflecting all costs and amounts billed to Authority under the contract at issue. Authority, its employees, officers, or representatives shall have the right upon written request and reasonable notice, to inspect and examine all of the vendor's books and records related to the contract. Such records shall be retained by vendor for at least five (5) years from the termination of the contract. In no event shall books and records be disposed of or destroyed of prior to five (5) years from the termination of the contract or during any dispute or claim between the Authority and vendor with regard to the contract at issue.
 - 1. In accordance with the New Jersey Office of the State Comptroller ("OSC") document retention policy *N.J.A.C.* 17:44-2.2 The vendor shall maintain all documentation related to products, transactions, or services under this contract for a period of five years from the date of final payment. Such records shall be made available to the OSC upon request.
- **K. TAXES**-The Authority is exempt from Federal Excise Tax, New Jersey State Sales and Use Tax and other tax as applicable.
- **L. TRANSFER OF BUSINESS**-It is understood by all parties that, if, during the term of the contract, the vendor disposes of its business by sale, transfer or by any means to another party, all obligations are transferred to such purchaser.

M. INTERAGENCY COOPERATIVE PURCHASING-Pursuant to *N.J.S.A.* 27:23-6.1(a), vendors may receive inquiries by the entities listed below, with respect to extending this contract to them based upon the same prices, terms, and conditions:

South Jersey Transportation Authority
New Jersey Sports & Exposition Authority
New Jersey Meadowlands Commission
New Jersey Water Supply Authority
Port Authority of New York & New Jersey
Delaware River Port Authority
Higher Education Student Assistance Authority

N. CONTRACT CHANGES-During the term of contract, no change will be permitted in any of its conditions and specifications unless the vendor receives written approval from the Director.

Should the vendor find at any time that existing conditions make modification in requirements necessary, the vendor shall promptly report such matter to the Director for consideration and decision.

- **O. SUBCONTRACTING OR ASSIGNMENT**-The contract may not be subcontracted or assigned by the vendor, in whole or in part, without the prior written consent of the Director. In the event that bidder proposes to subcontract some or all of the services to be provided under the contract, it shall state so in its bid and attach for approval a list of said subcontractors and an itemization of the goods and/or services to be supplied by them.
- **P. REJECTION OF BIDS**-Failure to comply with mandatory requirements of the bid shall be considered grounds for rejection. The Authority retains the right to reject any or all bids, to waive informalities and minor irregularities and to rebid the entire contract.
- **Q. LIABILITIES OR DEBTS OWED TO THE AUTHORITY-** The failure by any Contractor or subcontractor during the term of the Contract to satisfy in a timely manner any outstanding debts or fees owed to the Authority, whenever incurred, including but not limited to those related to nonpayment of tolls or administrative fees, as required by *N.J.A.C.* 19:9-1.19 and *N.J.A.C.* 19:9-9.2, shall be grounds for suspension or termination of the Contract, in the sole discretion of the Authority.

EXHIBIT A MANDATORY EQUAL EMPLOYMENT OPPORTUNITY LANGUAGE N.J.S.A. 10:5-31 et seq., N.J.A.C. 17:27

GOODS, PROFESSIONAL SERVICES AND GENERAL SERVICE CONTRACTS

During the performance of this contract, the contractor agrees as follows:

- A. The Contractor or Subcontractor, where applicable, will not discriminate against any employee or applicant for employment because of age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality, or sex. Except with respect to affectional or sexual orientation and gender identity or expression, the contractor will ensure that equal employment opportunity is afforded to such applicants in recruitment and employment and that employees are treated during employment without regard to their age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex. Such equal employment opportunity shall include, but not limited to the following: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided by the Public Agency Compliance Officer setting forth provisions of this nondiscrimination clause.
- B. The Contractor or Subcontractor, where applicable will, in all solicitations or advertisements for employees placed by or on behalf of the contractor, state that all qualified applicants will receive consideration for employment without regard to age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity, or expression, disability, nationality or sex.
- C. The Contractor or Subcontractor will send to each labor union with which it has a collective bargaining agreement a notice, to be provided by the agency contracting officer, advising the labor union of the Contractor's commitments under this chapter and shall post copies of the notice in conspicuous places available to employees and applicants for employment.
- D. The Contractor or Subcontractor, where applicable, agrees to comply with any regulations promulgated by the Treasurer pursuant to *N.J.S.A.* 10:5-31 et seq., as amended and supplemented from time to time, and the Americans with Disabilities Act.
- E. The Contractor or Subcontractor agrees to make good faith efforts to meet targeted county employment goals established in accordance with *N.J.A.C.* 17:27-5.2.
- F. The Contractor or Subcontractor agrees to inform in writing its appropriate recruitment agencies including, but not limited to, employment agencies, placement bureaus, colleges, universities and labor unions, that it does not discriminate on the basis of age, race, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex, and that it will discontinue the use of any recruitment agency which engages in direct or indirect discriminatory practices.

- G. The Contractor or Subcontractor agrees to revise any of its testing procedures, if necessary, to assure that all personal testing conforms with the principles of job-related testing, as established by the statutes and court decisions of the State of New Jersey and as established by applicable Federal law and applicable Federal court decisions.
- H. In conforming with the targeted employment goals, the Contractor or Subcontractor agrees to review all procedures relating to transfer, upgrading, downgrading and layoff to ensure that all such actions are taken without regard to age, creed, color, national origin, ancestry, marital status, affectional or sexual orientation, gender identity or expression, disability, nationality or sex, consistent with the statutes and court decisions of the State of New Jersey, and applicable Federal law and applicable Federal court decisions.
- I. The Contractor shall submit to the public agency, after notification of award but prior to execution of a goods and services contract, one of the following three documents:
 - i. LETTER OF FEDERAL AFFIRMATIVE ACTION PLAN APPROVAL
 - ii. CERTIFICATE OF EMPLOYEE INFORMATION REPORT
 - iii. EMPLOYEE INFORMATION REPORT FORM AA302

The Contractor and its Subcontractors shall furnish such reports or other documents to the Division of Public Contracts Equal Employment Opportunity Compliance as may be requested by the Division from time to time in order to carry out the purposes of these regulations, and public agencies shall furnish such information as may be requested by the Division of Public Contracts Equal Employment Opportunity Compliance for conducting a compliance investigation pursuant to **Subchapter 10 of the Administrative Code at** *N.J.A.C.* **17:27**

Submitted by:	
Firm Name:	
Signature:	
Print Name:	
Title:	
Date:	

EXHIBIT B AFFIRMATIVE ACTION INFORMATION SHEET

BIDDERS ARE REQUIRED TO SUBMIT ONE OF THE FOLLOWING FORMS RELATING TO COMPLIANCE WITH AFFIRMATIVE ACTION REGULATIONS. PLEASE COMPLETE AND RETURN THIS FORM AND ANY REQUIRED DOCUMENTS WITH THE BID.

1.	The bidder has a Federal Affirmative Action Plan Approval which consists of a valid letter from the United States Department of Labor Office of Federal Contract Compliance Programs (Good for one year of the date of letter).
	YES NO If Yes, a photocopy of the Letter of Approval is to be submitted with the bid.
	(OR)
2.	The bidder has submitted an Affirmative Action Employee Information Report (Form AA302) to the State Treasurer, and the State Treasurer has approved said report pursuant to <i>N.J.A.C.</i> 17:27-4.6.
	YES NO
	If Yes, a photocopy of the Certificate of Employee Information Report is to be submitted with the bid. (Expiration Date on Certificate) Certificate Number
	(OR)
3.	The bidder has submitted an Employee Information Report (Form AA302) to the State Treasurer, and the State Treasurer has not yet approved said report.
	YES NO If Yes, a photocopy of the Form AA302 is to be submitted with the bid.
	If you are the <u>successful</u> Proposer and have none of the above, please contact the Procurement and Materials Management Department at (732) 750-5300 ext. 8628 within five (5) days of notification of award for AA-302 Form. This AA-302 Form must be forwarded to the <u>States' Affirmative Action Office</u> with a copy returned to the Authority's Procurement and Materials Management Department.
-	gnature below certifies that one of the above forms of Affirmative Action evidence has been red, and all information contained above is correct to the best of my knowledge.
Signed_	Date Signed
Print N	ame and Title
Bidder'	's Company Name
Address	S
Telepho	one Number Fax Number

EXHIBIT C OWNERSHIP DISCLOSURE FORM

BIDDER/PROPOSER:

BID SOLICITATION:

<u>PART 1</u>
EASE COMPLETE THE QUESTIONS BELOW BY CHECKING EITHER THE "YES" R "NO" BOX. ALL PARTIES ENTERING INTO A CONTRACT WITH THE NEW RSEY TURNPIKE AUTHORITY ARE REQUIRED TO COMPLETE THIS FORM RSUANT TO N.J.S.A. 52:25-24.2
EASE NOTE THAT IF THE BIDDER/PROPOSER IS A NON-PROFIT ENTITY, THIS ORM IS NOT REQUIRED.
Are there any individuals, corporations, partnerships, or limited liability companies owning a 10% or greater interest in the Bidder/Proposer?
YES □ NO □
THE ANSWER TO QUESTION 1 IS "NO", PLEASE SIGN AND DATE THE FORM.
THE ANSWER TO QUESTION 1 IS "YES", PLEASE ANSWER QUESTIONS 2-4 CLOW.
Of those parties owning a 10% or greater interest in the Bidder/Proposer, are any of those parties individuals?
YES □ NO □
Of those parties owning a 10% or greater interest in the Bidder/Proposer, are any of those parties corporations, partnerships, or limited liability companies?
YES □ NO □
If your answer to Question 3 is "YES", are there any parties owning a 10% or greater interest in the corporation, partnership, or limited liability company referenced in Question 3?
YES □ NO □

IF ANY OF THE ANSWERS TO QUESTIONS 2-4 ARE "YES", PLEASE PROVIDE THE

REQUESTED INFORMATION IN PART 2.

PART 2

PLEASE PROVIDE FURTHER INFORMATION RELATED TO QUESTIONS 2-4 ANSWERED AS "YES".

If you answered "YES" for questions 2, 3, or 4 you must disclose identifying information related to the individuals, corporations, partnerships, and/or limited liability companies owning a 10% or greater interest in the Bidder/Proposer. Further, if one or more of these entities is itself a corporation, partnership, or limited liability company, you must also disclose all parties that own a 10% or greater interest in that corporation, partnership, or limited liability company. This information is required by statute.

INDIVIDUALS

NAME		DATE OF BIRTH
ADDRESS 1		
ADDRESS 2		
		ZIP
NAME		DATE OF BIRTH
ADDRESS 1		
ADDRESS 2		
CITY	STATE	ZIP
NAME_		DATE OF BIRTH
ADDRESS 1		
ADDRESS 2		
CITY	STATE	ZIP

Attach Additional Sheets if Necessary.

PART 2 continued

PARTNERSHIPS/CORPORATIONS/LIMITED LIABILITY COMPANIES

ENTITY NAME			
PARTNER NAME			
ADDRESS 1			
ADDRESS 2			
CITY	STATE	ZIP	
ENTITY NAME			
PARTNER NAME			
ADDRESS 1			
ADDRESS 2			
CITY	STATE	ZIP	
ENTITY NAME			
PARTNER NAME			
ADDRESS 1			
ADDRESS 2			
CITY	STATE	ZIP	

Attach Additional Sheets if Necessary.

In the alternative, to comply with the ownership disclosure requirement, a Bidder/Proposer with any direct or indirect parent entity which is publicly traded may submit the name and address of each publicly traded entity and the name and address of each person that holds a 10% or greater beneficial interest in the publicly traded entity as of the last annual filing with the federal Securities and Exchange Commission or the foreign equivalent, and, if there is any person that holds a 10% or greater beneficial interest , also shall submit links to the websites containing the last annual filings with the federal securities and Exchange Commission or the foreign equivalent and the relevant page number(s) of the filings that contain the information on each person that holds a 10 percent or greater beneficial interest. *N.J.S.A* 52:25-24.2.

CERTIFICATION

I, the undersigned, certify that I am authorized to execute this certification on behalf of the Bidder/Proposer, that the foregoing information and any attachments hereto, to the best of my knowledge are true and complete. I acknowledge that the New Jersey Turnpike Authority is relying on the information contained herein, and that the Bidder/Proposer is under a continuing obligation from the date of this certification through the completion of any contract(s) with the New Jersey Turnpike Authority to notify the New Jersey Turnpike Authority in writing of any changes to the information contained herein; that I am aware that it is a criminal offense to make a false statement or misrepresentation in this certification. If I do so, I will be subject to criminal prosecution under the law, and it will constitute a material breach of my agreement(s) with the New Jersey Turnpike Authority, permitting the New Jersey Turnpike Authority to declare any contract(s) resulting from this certification void and unenforceable.

Signature	Date	
Print Name and Title		
FEIN/SSN		

EXHIBIT D

State Contractor Political Contributions Compliance Public Law 2005, Chapter 51 and Executive Order 117

In order to safeguard the integrity of State government procurement by imposing restrictions to insulate the award of State contracts from political contributions that pose the risk of improper influence, purchase of access, or the appearance thereof, Executive Order 134 (McGreevey) was signed on September 22, 2004 and became effective October 15, 2004. EO134 was applicable to all State agencies, the principal departments of the executive branch, any division, board, bureau, office, commission within or created by a principal executive branch department, and any independent State authority, board, commission, instrumentality, or agency. EO134 was superseded by P.L. 2005, c. 51, signed into law on March 22, 2005 ("Chapter 51"). In September 2008, Executive Order 117 (Corzine) was signed and became effective November 15, 2008. EO117, which applies only prospectively, extends Chapter 51's political contribution restrictions by expanding the definition of "business entity" to include, for example, more corporate shareholders and sole proprietors. EO117 and Chapter 51 contain restrictions and reporting requirements that will necessitate a thorough review of their provisions by bidders.

Pursuant to the requirements of Chapter 51 and EO117, the terms and conditions set forth in this Exhibit are material terms of any contract entered into by the Authority.

DEFINITIONS

For the purpose of this Exhibit, the following shall be defined as follows:

- a) "Contribution" means a contribution reportable by the recipient under the New Jersey Campaign Contributions and Expenditures Reporting Act, <u>P.L.</u> 1973, <u>c.</u> 83, *N.J.S.A.* 19:44A-1 et seq., and implementing regulations set forth at *N.J.A.C.* 19:25-7 and *N.J.A.C.* 19:25-10.1 et seq., made on or after October 15, 2004. As of January 1, 2005, contributions in excess of \$300 are reportable.
- b) "Business Entity" means any natural or legal person; business corporation (and any officer, person, or business entity that owns or controls 10% or more of the corporation's stock); professional services corporation (and any of its officers or shareholders); limited liability company (and any members); general partnership (and any partners); limited partnership (and any partners); in the case of a sole proprietorship: the proprietor; a business trust, association or any other legal commercial entity organized under the laws of New Jersey or any other state or foreign jurisdiction, including its principals, officers, or partners. The definition of a business entity also includes (i) all principals who own or control more than 10 percent of the profits or assets of a business entity; (ii) any subsidiaries directly or indirectly controlled by the business entity; (iii) any political organization organized under section 527 of the Internal Revenue Code that is directly or indirectly controlled by the business entity, other than a candidate committee, election fund, or political party committee; and (iv) if a business entity is a natural person, that person's spouse, civil union partner or child, residing in the same household, except for contributions by spouses, civil union partners, or resident children to a candidate for whom the contributor is eligible to vote, or to a political party committee within whose jurisdiction the contributor resides.

PROHIBITION ON CONTRACTS/BREACH OF EXISTING CONTRACT

As set forth in Chapter 51 and EO117, the Authority shall not enter into a contract to procure from any Business Entity services or any material, supplies or equipment, or to acquire, sell or lease any land or building, where the value of the transaction exceeds \$17,500, if that Business Entity has solicited or made any contribution of money, or pledge of contribution, including in-kind contributions, to a candidate committee and/or election fund of any candidate for or holder of the public office of Governor or Lieutenant Governor, or to any State, county or municipal political party committee, or legislative leadership committee during specified time periods.

Further, it shall be a breach of the terms of any contract with the Authority for any Business Entity who has been awarded the contract, during the term of the contract or any extension thereof, to:

- (i) make or solicit a contribution in violation of Chapter 51 or EO117;
- (ii) knowingly conceal or misrepresent a contribution given or received;
- (iii) make or solicit contributions through intermediaries for the purpose of concealing or misrepresenting the source of the contribution;
- (iv) make or solicit any contribution on the condition or with the agreement that it will be contributed to a campaign committee or any candidate of holder of the public office of Governor or Lieutenant Governor, or to any State, county or municipal party committee, or legislative leadership committee;
- (v) engage or employ a lobbyist or consultant with the intent or understanding that such lobbyist or consultant would make or solicit any contribution, which if made or solicited by the Business Entity itself, would subject that entity to the restrictions of Chapter 51 or EO117;
- (vi) fund contributions made by third parties, including consultants, attorneys, family members, and employees;
- (vii) engage in any exchange of contributions to circumvent the intent of Chapter 51 or EO117; or
- (viii) directly or indirectly through or by any other person or means, do any act which would subject that entity to the restrictions of Chapter 51 or EO117.

CERTIFICATION AND DISCLOSURE REQUIREMENTS

Prior to the award of any contract or agreement, the Authority shall notify any Business Entity to which it intends to award a contract of the need to submit to the Authority a completed Certification and Disclosure of Political Contributions form, as issued by the State Treasurer. The <u>intended</u> <u>awardee</u> will receive the applicable form from the Authority's Purchasing Department <u>to be</u> completed and returned to the Authority for submission to the State Treasurer.

In completing this form, the Business Entity must certify that no contributions prohibited by Chapter 51 or EO117 have been made by the Business Entity and must report all contributions the Business Entity made during the preceding four years to any political organization organized under 26 <u>U.S.C.</u> § 527 of the Internal Revenue Code that also meets the definition of a "continuing political committee" within the meaning of *N.J.S.A.* 19:44A-3(n) and *N.J.A.C.* 19:25-1.7. Failure

to submit the required forms will preclude award of the contract at issue, as well as future contract opportunities.

Upon approval by the State Treasurer, the Authority will issue a contract. However, if the State Treasurer determines that any contribution or action by a Business Entity poses a conflict of interest in the awarding of the contract or agreement at issue, the State Treasurer shall disqualify the Business Entity from award of such contract.

Once approved by the State Treasurer, a Business Entity's Political Contributions Certification is valid for a two (2) year period from the date of approval. If, prior to the award of a contract, the State Treasurer confirms to the Authority that the intended awardee has an approved Certification that will remain valid for the term of the contract, the Authority may waive the requirement that the awardee complete an additional Certification and Disclosure of Political Contributions form.

Any Business Entity entering into a contract with the Authority is required, on a continuing basis, to report to the Authority any contributions it makes during the term of the contract, and any extension(s) thereof, at the time any such contribution is made. Such reports shall be subject to review by the Authority and the State Treasurer. If the State Treasurer determines that any such contribution poses a conflict of interest, such contribution shall be deemed a material breach of the contract or agreement at issue.

<u>EXHIBIT E</u> <u>NEW JERSEY ELECTION LAW ENFORCEMENT COMMISSION</u> <u>REQUIREMENT FOR DISCLOSURE OF POLITICAL CONTRIBUTIONS</u>

All business entities are advised of their responsibility to file on annual disclosure statement of political contributions with the New Jersey Election Law Enforcement Commission (ELEC) pursuant to N.J.S.A. 19:44A-20.27 if they receive contracts in excess of \$50,000.00 from public entities in a calendar year. Business entities are responsible for determining if filing is necessary. Additional information on this requirement is available from ELEC at 888-313-3532 or at www.elec.state.nj.us

DISCLOSURE OF CONTRIBUTIONS TO NEW JERSEY ELECTION LAW ENFORCEMENT COMMISSION IN ACCORDANCE WITH N.J.S.A. 19:44A-20.27

The undersigned Bidder submitting the bid for the goods/services herein hereby acknowledges its responsibility to file an annual disclosure statement of political contributions with the New Jersey Election Law Enforcement Commission (ELEC) pursuant to *N.J.S.A.* 19:44A-20.27 if in receipt of contracts in excess of \$50,000.00 from public entities in a calendar year. Bidder further acknowledges that business entities are solely responsible for determining if filing is necessary and that all statements contained in said bid and in this certification, are true and correct, and made with full knowledge that the New Jersey Turnpike Authority relies upon the truth of the statements contained in said bid and in statements contained in this certification in awarding the contract at issue.

I certify that I am authorized to make the foregoing statements on behalf of the Bidder and that the foregoing statements made by me are true. I am aware that if any of the foregoing statements made by me are willfully false, I am subject to punishment.

AUTHORIZED SIGNATURE:
Print Name and Title:
Bidder:
Date:

EXHIBIT F SMALL/MINORITY/WOMAN OWNED BUSINESS ENTERPRISE

If your firm is registered with the State of New Jersey as a Small Business Enterprise (SBE) and/or certified as a Woman Business Enterprise (WBE), a Minority Business Enterprise (MBE), a Veteran Owned Business (VOB) or as a Disabled Veteran Owned Business (DVOB), you must send a copy of the Registration/Certification Form(s) with your quotation.

Please check off the gross receipt category of your business if registered as an SBE

SBE CATEGORY 1	\$0- \$500,000	
SBE CATEGORY 2	\$500,001 thru \$5,000,000	
SBE CATEGORY 3	\$5,000,001 thru \$12,000,000	
NOT APPLICABLE		
SBE Registration #		
Please check below if applica	ble	
W B E M B E	VOB DVOB	
	COMPANY	
	COMPANY	
	SIGNATURE	
	NAME	
	TITLE	
	DATE	

EXHIBIT G VENDOR DISCLOSURE FORM

Please be advised that in accordance with *N.J.S.A.* 52:34-13.2, the New Jersey Turnpike Authority has developed this form under the policy and procedures directed under this Order. In entering into contracts, the State contracting agencies must consider the requirements of New Jersey's contracting laws, the best interests of the State of New Jersey and its citizens, as well as applicable federal and international requirements.

The State contracting agencies shall ensure that all vendors seeking to enter into any contract in which services are procured on behalf of the State of New Jersey must disclose:

- A. The location by country where services under the contract will be performed; and
- B. Any subcontracting of services under the contract and the location by country where any subcontracted services will be performed.

THE LOCATION BY COUNTRY WHERE SERVICES UNDER THIS CONTRACT WILL BE PERFORMED:

Contractor Name:	
Address:	
Subcontractor #2 Name:	
Address:	
Country:	
(For additional sul	becontractors, attach additional copies of this form)
I certify that all information is	true and correct to the best of my knowledge.
Signature:	
Print Name:	Title:

EXHIBIT G-1 NEW JERSEY TURNPIKE AUTHORITY DISCLOSURE OF INVESTMENT ACTIVITIES IN IRAN

NAME OF CONTRACTOR /BIDDER:
PART 1: CERTIFICATION
CONTRACTORS/BIDDERS <u>MUST COMPLETE</u> PART 1 BY CHECKING <u>EITHER BOX</u> .
FAILURE TO CHECK ONE OF THE BOXES SHALL RENDER THE PROPOSAL NON- RESPONSIVE.
Pursuant to Public Law 2012, c. 25, any person or entity that submits a bid or proposal or otherwise proposes to enter into or renew a contract must complete the certification below to attest, under penalty of perjury, that neither the person or entity, nor any of its parents, subsidiaries, or affiliates, is identified on the Department of Treasury's Chapter 25 list as a person or entity engaging in investment activities in Iran. The Chapter 25 list follows this certification and can also be found on the State of New Jersey, Department of Treasury, Division of Purchase and Property website at http://www.state.nj.us/treasury/purchase/pdf/Chapter25List.pdf . Contractors/Bidders mustreview this list prior to completing the below certification. BIDDER'S PROPOSAL NON-RESPONSIVE . If the Authority finds a person or entity to be in violation of law, it shall take action as may be appropriate and provided by law, rule or contract, including but not limited to imposing sanctions, seeking compliance, recovering damages, declaring the party in default and seeking debarment or suspension of the party.
PLEASE CHECK THE APPROPRIATE BOX:
☐ I certify, pursuant to Public Law 2012, c. 25, that neither the contractor/bidder listed
above nor any of the contractor's/bidder's parents, subsidiaries, or affiliates is <u>listed</u> on the N.J. Department of the Treasury's list of entities determined to be engaged in prohibited activities in Iran pursuant to P.L. 2012, c. 25 ("Chapter 25 List"). I further certify that I am the person listed above, or I am an officer or representative of the entity listed above and I am authorized to make this certification on its behalf. <i>I will skip Part 2 and sign and complete the CERTIFICATION below.</i>
<u>OR</u>
I am unable to certify as above because the contractor/bidder and/or one or more of its parents, subsidiaries, or affiliates is listed on the Department's Chapter 25 list. I will provide a detailed, accurate and precise description of the activities in Part 2 below and sign and complete the CERTIFICATION below. Failure to provide such will result in the proposal
being rendered a non-responsive and appropriate penalties, fines and/or sanctions will be assessed

as provided by law.

Part 2: PLEASE PROVIDE FURTHER INFORMATION RELATED TO INVESTMENT ACTIVITIES IN IRAN

You must provide a detailed, accurate and precise description of the activities of the bidding person/entity, or one of its parents, subsidiaries or affiliates, engaging in the investment activities in Iran outlined above by completing the requested information below. Please provide thorough answers to each question. If you need to make additional entries, provide the requested information on a separate sheet

NameRelationship to Contractor/Bidder		
Description of Activities		
Duration of Engagement	Anticipated Cessation Date	
Contractor/Bidder Contact Name	eContact Phone Number	
I, being duly sworn upon my or and any attachments thereto to I am authorized to execute the entity. I acknowledge that the the information contained her obligation from the date of this the Authority to notify the Aut contained herein. I acknowledge statement or misrepresentation subject to criminal prosecution breach of my agreement(s) we	CERTIFICATION Auth, hereby represent and state that the foregoing information of the best of my knowledge are true and complete. I attest that its certification on behalf of the above referenced person of New Jersey Turnpike Authority ("Authority") is relying or rein and thereby acknowledge that I am under a continuing its certification through the completion of any contracts with hority in writing of any changes to the answers of information ge that I am aware that it is a criminal offense to make a false on in this certification, and if I do so, I recognize that I am on under the law and that it will also constitute a material ith the Authority and that the Authority at its option maying from this certification void and unenforceable.	
FULL NAME (print):	SIGNATURE	
TITLE.	DATE.	



EXHIBIT G-2

CERTIFICATION OF NON-INVOLVEMENT IN PROHIBITED ACTIVITIES IN RUSSIA OR BELARUS PURSUANT TO P.L.2022, c.3

CONTRA	ACT / BID SOLICITATION TITLE	
CONTR	ACT / BID SOLICITATION No.	
	CHECK THE APPROPRIATE BOX	<u>(</u>
	I, the undersigned , am authorized by the person or entity se above, to certify that the Bidder is not engaged in prohibite defined in P.L.2022, c.3, section 1.e, except as permitted by	d activities in Russia or Belarus as such term is
	I understand that if this statement is willfully false, I may be section 1.d.	subject to penalty, as set forth in P.L.2022, c.3,
OR		
	I, the undersigned am unable to certify above because the person or entity seeking to enter into or renew the contract identified above, or one of its parents, subsidiaries, or affiliates may have engaged in prohibited activities in Russia or Belarus. A detailed, accurate and precise description of the activities is provided below.	
	Failure to provide such description will result in the Proposal being rendered as non-responsive, and the Authority will not be permitted to contract with such person or entity, and if a Proposal is accepted or contract is entered into without delivery of the certification, appropriate penalties, fines and/or sanctions will be assessed as provided by law.	
	Description of Prohibited Activity	
	Attach Additional Sheets If Necessary.	
engaging If the Bi engaged be requi	ertify that the Bidder is engaged in activities prohibited by P.L g in any prohibited activities and on or before the 90 th day after dder does not provide the updated certification or at that tin d in prohibited activities, the State shall not award the busines red to terminate any contract(s) the business entity holds wit P.L. 2022, c. 3.	this certification, shall provide an updated certification. ne cannot certify on behalf of the entity that it is not sentity any contracts, renew any contracts, and shall
Signatur	re of Authorized Representative	<u>Date</u>
Print Na	me and Title of Authorized Representative	
Bidder N	lame	

¹ Engaged in prohibited activities in Russia or Belarus" means (1) companies in which the Government of Russia or Belarus has any direct equit y share; (2) having any business operations commencing after the effective date of this act that involve contracts with or the provision of goods or services to the Government of Russia or Belarus; (3) being headquartered in Russia or having its principal place of business in Russia or Belarus, or (4) supporting, assisting or facilitating the Government of Russia or Belarus in their campaigns to invade the sovereign country of Ukraine, either through in-kind support or for profit.

EXHIBIT H NOTICE TO ALL BIDDERS SET-OFF FOR STATE TAX

Please be advised that pursuant to <u>P.L.</u> 1995, <u>c.</u> 159, effective January 1, 1996 and notwithstanding any provision of the law to the contrary, whenever any taxpayer, partnership, or S corporation under contract to provide goods or services or construction projects to the State of New Jersey or its agencies or instrumentalities, including the legislative and judicial branches of State government, is entitled to payment for those goods or services or construction projects and at the same time the taxpayer, or the partner or shareholder of that entity, is indebted for any State tax, the Director of the Division of Taxation shall seek to set-off that taxpayer's, partner's or shareholder's share of the payment due to the taxpayer, partnership, or S corporation. The amount of set-off shall not allow for the deduction of any expenses or other deductions which might be attributable to a partner or shareholder subject to set-off under this act. No payment shall be made to the taxpayer, the provider of goods or services, or the contractor or subcontractor of construction projects pending resolution of the indebtedness.

The Director of Division of Taxation shall give notice of the set-off to the taxpayer, the provider of goods or services, or the contractor or subcontractor of construction projects and provide an opportunity for a hearing with thirty (30) days of such notice under the procedures for protests established under *N.J.S.A.* 54:49-18. No requests for conference, protest or subsequent appeal to the Tax Court from any protest under this section shall stay the collection of the indebtedness. Interest that may be payable by the State pursuant to <u>P.L.</u> 1987, <u>c.</u> 184, *N.J.S.A.* 52:32-32 et seq. to the taxpayer, the provider of goods or services, or the contractor or subcontractor of construction projects shall be stayed.

"I HAVE BEEN ADVISED OF THIS NOTICE."

COMPANY	
SIGNATURE	
NAME	
TITLE	
DATE	

EXHIBIT I

LETTER OF SURETY

KNOW ALL MEN BY THESE PRESENTS, that we, the undersigned

as PRINCIPAL: and
as Surety and duly qualified to transact business in the State of New Jersey, are hereby held and firmly bound unto the New Jersey Turnpike Authority in the sum by which the amount of the Contract, covering the attached proposal, properly and lawfully executed by and between the New Jersey Turnpike Authority and some third party, may exceed the amount bid by the Principal for the payment of which, well and truly to be made, we hereby jointly and severally bind ourselves, our heirs, executors, administrators, successors and assigns.
Signed, thisday ofA.D.
Two Thousand and
THE CONDITION OF THE ABOVE OBLIGATION IS SUCH that whereas the Principal has submitted to the New Jersey Turnpike Authority a certain Proposal, attached hereto and hereby made a part hereof, to enter into a Contract in writing for Contract No of the New Jersey Turnpike Authority;
NOW, THEREFORE,
(a) If said Proposal shall be rejected by the New Jersey Turnnike Authority or in the

- (a) If said Proposal shall be rejected by the New Jersey Turnpike Authority, or in the alternative,
- (b) If said Proposal shall be accepted by the New Jersey Turnpike Authority, and the Principal shall duly execute the Contract Agreement and furnish the required Contract Bond, within the stipulated time,

Then this obligation shall be void, otherwise the same shall remain in force and effect; it being expressly understood and agreed that the liability of the Surety for any and all claims hereunder shall, in no event, exceed the amount of this obligation as herein stated.

The Surety, for value received, hereby stipulates and agrees that the obligation of said Surety and its bond shall be in no way impaired or affected by any extension of the time within which the Authority may accept such Proposal; and said Surety does hereby waive notice of any such extension.

IN WITNESS WHEREOF, the Principal and the Surety have hereunto set their hands and seals, and such of them as are corporations have caused their corporate seals to be hereto affixed and these presents to be signed by their proper officers, the day and year first set forth above.

[Corporate Seal]		
WITNESS OR ATTEST:		
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	Principal	_
[Corporate Seal]		
[Corporate Sear]		
WITNESS OR ATTEST:		
	Surety	
	Surety	

EXHIBIT J

PROPOSAL BOND

KNOW ALL MEN BY THESE PRESENTS, that we, the undersigned

as PRINCIPAL: and
as Surety and duly qualified to transact business in the State of New Jersey, are hereby held and firmly bound unto the New Jersey Turnpike Authority in the sum of
Dollars and
Cents \$ for the payment of which, well and truly to be made, we hereby jointly and severally bind ourselves, our heirs, executors, administrators, successors, and assigns.
Signed, thisday ofA.D.
Two Thousand and
THE CONDITION OF THE ABOVE OBLIGATION IS SUCH that whereas the Principal has submitted to the New Jersey Turnpike Authority a certain Proposal, attached hereto and hereby made a part hereof, to enter into a Contract in writing for Contract No of the New Jersey Turnpike Authority;
NOW, THEREFORE,
(a) If said Proposal shall be rejected by the New Jersey Turnpike Authority, or in the alternative,
(b) If said Proposal shall be accepted by the New Jersey Turnpike Authority and the Principal shall duly execute the Contract Agreement and furnish the required Contract Bond, within the

Then this obligation shall be void, otherwise the same shall remain in force and effect; it being expressly understood and agreed that the liability of the Surety for any and all claims hereunder shall in no event, exceed the amount of this obligation as herein stated.

stipulated time,

The Surety, for value received, hereby stipulates and agrees that the obligation of said Surety and its bond shall be in no way impaired or affected by any extension of the time within which the Authority may accept such proposal; and said Surety does hereby waive notice of any such extension.

IN WITNESS WHEREOF, the Principal and the Surety have hereunto set their hands and seals, and such of them as are corporations have caused their corporate seals to be hereto affixed and these presents to be signed by their proper officers, the day and year first set forth above.

[Corporate Seal]
WITNESS OR ATTEST
Principal
Corporate Seal]
WITNESS OR ATTEST:
Surety

EXHIBIT K CONTRACT BOND

KNOW ALL MEN BY THESE PRESENTS:

That we,		
Duly organized under	the Laws of the	
	(An indiv	vidual, a partnership, a corporation)
State of	and having a usual pla	ace of
	at	as
Principal, and		a
corporation duly orga	nized under the Laws of the Sta	ate of and duly authorized to do
		ual place of business at
		and obligated unto the New Jersey Turnpike
		lawful money of the United States of
		e bind ourselves and each of us, our heirs,
	1 4	pintly and severally, firmly by these presents.
The condition of the a	above obligation is such that wh	hereas, the above named Principal did on the
		ntract with the Obligee, New Jersey Turnpike
		which said contract is made part
	e as though set forth herein.	<u> </u>
Now, if the said Prin	ncipal shall well and faithfully	y do and perform the things agreed by the
Principal to be done a	nd performed according to the to	terms of said contract, and shall pay all lawful

Now, if the said Principal shall well and faithfully do and perform the things agreed by the Principal to be done and performed according to the terms of said contract, and shall pay all lawful claims of laborers and other beneficiaries as defined by *N.J.S.A* 2A:44-143 for labor performed or materials, provisions, provender of other supplies, or teams, fuels, oils, implements or machinery furnished, used or consumed in the carrying forward, performing or completing of said contract, we agreeing and assenting that this undertaking shall be for the benefit of laborers and any beneficiary as defined in *N.J.S.A* 2A:44-143 having a just claim, as well as, for the Obligee herein, then this obligation shall be void; otherwise, the same shall remain in full force and effect; it being expressly understood and agreed that the liability of the Surety for any and all claims hereunder shall in no event exceed the penal amount of this obligation as herein stated.

The said Surety hereby stipulates and agrees that no modifications, omissions, or additions in or to the terms of the said contract or in or to the plans or specifications therefore shall in anywise affect the obligation of said Surety on its bond, and the Surety hereby waives notice of same.

IN WITNESS WHEREOF, we h	ave hereunto set our hands and seals	
thisday of	in the year 20	
WITNESS OR ATTEST		
	PRINCIPAL	
[CORPORATE SEAL]	FRINCIFAL	
WITNESS OR ATTEST:		
[CORPORATE SEAL]	SURETY	

EXHIBIT L CERTIFICATION AND REQUEST FOR WAIVER OF THE COMPREHENSIVE AUTOMOBILE LIABILITY INSURANCE REQUIREMENT

Purchase Requisition #	
Liability Insurance policy for the above referenced below (hereinafter, "the Compara recognized, commercial third party shipp Air Borne Express, etc) to deliver all Good certification, a representation is made that rewill be used for the delivery of any goods to made will be restricted to the use of third p	V Jersey Turnpike Authority's Comprehensive Automobile berence Purchase Requisition. I certify that if the company my") is the successful low bidder the Company will utilize ther (i.e. UPS, Federal Express, DHL, U.S. Postal Service, do to the New Jersey Turnpike Authority. By signing this no vehicle either owned, rented or leased by the Company the New Jersey Turnpike Authority, and that, any delivery parties providing package delivery service in the ordinary ter of Comprehensive Automobile Liability Insurance is
	Company (insert name of Company)
	By: (print and sign name)
	Title
	Date
	Date

EXHIBIT M

INSTRUCTIONS FOR DIRECT PAYMENTS (ACH CREDITS)

<u>PLEASE PRINT ALL ENTRIES</u> (except for signature)

COMPANY NAME – Enter your company's name as registered with the New Jersey Turnpike Authority.

NJTA VENDOR ID NUMBER – Enter the number assigned to your company by the New Jersey Turnpike Authority*.

TELEPHONE NUMBER - Enter your telephone number, including area code.

EMAIL ADDRESS - Enter your email address. You will receive detailed notification of ACH payment.

DEPOSITORY NAME – Enter the name of your depository bank/financial institution.

BRANCH - Enter the name of your bank's branch office/location.

CITY/STATE/ZIP CODE – Enter your bank's address.

ROUTING NUMBER (DFI ID) – Enter your bank's routing number. This is your bank's nine position American Banking Association number, also known as the bank transit code.

ACCOUNT NUMBER – Enter your checking or savings account number. This is a variable length field.

NAME AND TITLE— Enter the name and title of the person who has the authority to accept ACH payment as an alternative to receiving check payment for your company.

AUTHORIZED SIGNATORY – Enter your signature.

If you require assistance, please call Carol Sabanos at (732) 750-5300, ext. 8149 or email her at achvendor@njta.

Following completion, forward the form (attached with the required <u>original</u> voided check or bank letter) to: New Jersey Turnpike Authority, ATTN: Accounts Payable, Finance Department/AP, PO Box 5042, Woodbridge, NJ 07095-5042 or you may scan and email the completed form (with the required <u>original</u> voided check or bank letter) to <u>achvendor@njta.</u>

New Jersey Turnpike Authority ATTN: Accounts Payable, Finance Department PO Box 5042 Woodbridge, NJ 07095-5042

Revised JP 02//2019

AUTHORIZATION AGREEMENT FOR DIRECT PAYMENTS (ACH CREDITS)		
Company Name	NJTA Vendor ID	
Telephone Number	Email Address	
I (we) hereby authorize New Jersey Turnpike Authority (NJTA) to initiate ACH credit entries to my (our) [] Checking Account / [] Savings Account (select one) indicated below at the depository financial institution named below, hereafter called DEPOSITORY.		
I (we) acknowledge that that origination of ACH transactions to my (our) account must comply with the provisions of U.S. law.		
Depository Name	Branch	
City	State Zip	
Routing Number (DFI ID)	Account Number	
This authorization is to remain in full force and effect until New Jersey Turnpike Authority (NJTA) has received written notification from me (or either of us) of its termination in such time and in such manner so as to afford New Jersey Turnpike Authority and DEPOSITORY a reasonable opportunity to act on it.		
Name(s)(please	Title	
(please	orint)	
Date Auth	orized Signatory	
PLEASE INCLUDE AN ORIGINAL VOIDED CHECK OR BANK LETTER WITH THIS FORM.		
For NJTA use only:		
Received by:	Date:	

Revised JP 02/2019